

Front adapters - FLKM 14-PA-S300/AN - 2302722

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE front adapter, for SIMATIC S7-300 analog I/O cards, 2 x 8 channels can be connected.

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 918224
GTIN	4017918918224

Technical data

General

Max. permissible operating voltage	60 V AC/DC
Max. permissible current	1 A (per path)
Max. permissible total current	2 A (per Byte, for supply via connector)
Mounting position	any

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Connection data 1

Connection name	Controller level
Channels which can be connected	32

Supported controller

Controller	SIEMENS S7-300 / ET 200 M
- suitable I/O card	6ES7 336-4GE00-0AB0

Standards and Regulations

Standards/regulations	IEC 60664
Degree of pollution	2

Front adapters - FLKM 14-PA-S300/AN - 2302722

Technical data

Standards and Regulations


Overvoltage category	II
----------------------	----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Circuit diagram



Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal current I _N	1 A		
Nominal voltage U _N	125 V		

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal current I _N	1 A		
Nominal voltage U _N	125 V		

Front adapters - FLKM 14-PA-S300/AN - 2302722

Approvals

EAC



RU C-
DE.A*30.B.01742

cULus Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>