

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

—, — .

© COPYRIGHT — By —

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

H

—

A

INITIAL RELEASE

12NOV2013

GSK

BvH

A1

ECR—14—011671

14AUG2014

GSK

BvH

NOTES:

Tolerances cable lengths:


0m to 0.5m +30mm


0.5m to 1.0m +50mm

1.0m to 3.0m +100mm

< 3.0m +1.5%

A





VIEW 'A'

TECHNICAL DATA

Operating voltage

max. 30 V AC/DC

Operating current per contact

max. 4 A

Locking of ports

Screw thread M8 x 1 mm (recommended torque 0.4 Nm) self—securing

Protection

IP65 and IP67 when plugged and screwed down (EN 60529)

PUR CABLE

No./diameter of wires

4 x 0.25 mm²

Wire isolation

PP (br, wh, bl, bk)

C—track properties

5 million

Jacket

PUR (UL/CSA)

Outer diameter

approx. 4.4 mm

Bend radius (moving)

10 x outer diameter

Temperature range (fixed)

—40...+80 °C

Temperature range (mobile)

—25...+80 °C

PVC CABLE

No./diameter of wires

4 x 0.25 mm²

Wire isolation

PVC (br, wh, bl, bk)

C—track properties

Jacket

PVC (UL/CSA)

Outer diameter

approx. 4.8 mm

Bend radius (moving)

10 x outer diameter

Temperature range (fixed)

—30...+80 °C

Temperature range (mobile)

—5...+80 °C

4 pos

10mtr

5mtr

3mtr

1.5mtr

PVC

Black

1—2273002—4

4x22AWG PVC 10.0m

8

1—2273002—3

4x22AWG PVC 5.0m

7

1—2273002—2

4x22AWG PVC 3.0m

6

1—2273002—1

4x22AWG PVC 1.5m

5

4 pos

10mtr

5mtr

3mtr

1.5mtr

PUR

Black

2273002—4

4x22AWG PUR 10.0m

4

2273002—3

4x22AWG PUR 5.0m

3

2273002—2

4x22AWG PUR 3.0m

2

2273002—1

4x22AWG PUR 1.5m

1

CONTACT LAYOUT

Male

1

2

3

4

1

2

4

3

flexible wire brown (+)

flexible wire white (N/C)


flexible wire black (N/O)

flexible wire blue (—)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± —

1 PLC ± —

2 PLC ± —

3 PLC ± —

4 PLC ± —

ANGLES ± —

FINISH —

MATERIAL

—

DWN

12NOV2013

SATHISH KUMAR .G

CHK

12NOV2013

B.VELDHOVEN

APVD

12NOV2013

A.VAN ZANDVOORT

PRODUCT SPEC

108—19483

APPLICATION SPEC

114—32127

WEIGHT

—

CUSTOMER DRAWING

TE Connectivity

M8 X 1.0 STRAIGHT PLUG PIGTAIL

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=2273002

—

SCALE

NTS

SHEET

1 OF 1

REV

A1

1470—19 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2273002-1](#)