

Torque screwdriver TorqueFix®



○ permanently pre-set torque limit

2850

Order-No.	Nm	±%	⊙	mm	mm	mm	mm	mm	mm
26925	0,4	6%	4	112	23				1
26127	0,5	6%	4	112	23				1
26047	0,6	6%	4	112	23				1
26327	0,8	6%	4	112	23				1
26048	0,9	6%	4	112	23				1
26133	1,1	6%	4	119	30				1
26049	1,2	6%	4	119	30				1
26901	1,5	6%	4	119	30				1
26051	2,0	6%	4	119	30				1
26128	2,5	6%	4	119	36				1
26052	3,0	6%	4	126	36				1
26129	3,8	6%	4	126	36				1
26053	5,0	6%	4	132	41				1
26130	5,5	6%	4	132	41				1
34533	6,0	6%	4	132	41				1
26131	7,2	6%	4	132	41				1

DIN EN ISO 6789.

Torque screwdriver set TorqueFix®



Cable key for circular plug connector permanently pre-set torque limit 2-pcs.

2850

Order-No.	Nm	⊙	mm	mm	mm	mm	mm	mm
36846	0,4	9	230	78	112	23		1
36847	0,6	13	230	78	112	23		1

DIN EN ISO 6789.

Torque screwdriver easyTorque



○ permanently pre-set torque limit

2920

Order-No.	Nm	±%	⊙	mm	mm	mm	mm	mm
36229	0,5	10%	4	130	34			1
36230	0,6	10%	4	130	34			1
36240	0,9	10%	4	130	34			1
36231	1,1	10%	4	130	34			1
36233	1,2	10%	4	130	34			1
36234	1,4	10%	4	130	34			1
36235	2,0	10%	4	130	34			1
36236	2,5	10%	4	130	34			1
36237	3,0	10%	4	130	34			1
36238	3,8	10%	4	130	34			1
36320	4,0	10%	4	130	34			1
36321	4,5	10%	4	130	34			1
36239	5,0	10%	4	130	34			1

INFOBOX: TorqueVario®-S



Variably settable torque tools.

- For controlled fastening in a large range of applications.
- Torque value is continuously adjustable thanks to the torque setter adjusting tool.
- Distinctly audible and perceptible click signal when set torque is reached.
- Each Wiha screwdriver handle provides a perfectly correlated ratio of guidance, speed and torque for any fastening task.
- Certified individual item testing directly after on-site production.
- Broad selection of interchangeable blades and adapter blades.

INFOBOX: TorqueFix®



Permanently pre-set torque tools.

- For controlled fastening, e.g. in series production or repetitive usage.
- Distinctly audible and perceptible click signal when set torque is reached.
- Each Wiha screwdriver handle provides a perfectly correlated ratio of guidance, speed and torque for any fastening task.
- Broad selection of interchangeable blades and adapter blades.