

Jumper - BRIDGE- 6 - 2900750

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



3-phase loop bridge for 6 modules from the CONTACTRON family with screw connection and 22.5 mm housing width.

Figure shows variant for 4 modules

Why buy this product

- Only suitable for CONTACTRON series with screw connection ELR H3...-SC-..., ELR H5...-SC-..., ELR (W)3..., EMM...IFS
- Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- Considerable reduction in wiring
- Up to 575 V AC/3 x 25 A



Key commercial data

Packing unit	1 pc
GTIN	 4 046356 528269
Weight per Piece (excluding packing)	136.28 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Length of the connecting cable	0.3 m
--------------------------------	-------

General

Nominal voltage U_N	575 V AC
Nominal current I_N	25 A
Number of bridgeable modules	6

Classifications

eCl@ss

eCl@ss 4.0	27371190
------------	----------

Jumper - BRIDGE- 6 - 2900750

Classifications

eCl@ss

eCl@ss 4.1	27371190
eCl@ss 5.0	27371692
eCl@ss 5.1	27371692
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	30211802
UNSPSC 7.0901	39121402
UNSPSC 11	39121402
UNSPSC 12.01	39121402
UNSPSC 13.2	39121402

Drawings

Application drawing

