

## Controller - AXC 1050 - 2700988

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Axio control for direct open-loop control of Axioline I/Os. With 2 Ethernet interfaces and programming capabilities according to IEC 61131-3. Complete with connector connector and labeling field.

### Product Description


The AXC 1050 modular small-scale controller for the Axioline I/O system is fast, robust, and easy, i.e., it is consistently designed for maximum performance, easy handling, and use in harsh industrial environments.

### Why buy this product

- ✓ PROFINET controller (up to 8 devices) or PROFINET device
- ✓ Modbus/TCP-Client
- ✓ Numerous protocols supported such as: http, https, FTP, SNMP, SMTP, SQL, MySQL, DCP, etc.
- ✓ Free engineering with PC Worx Express (IEC 61131-3)
- ✓ Up to 63 AXIO I/O modules can be mounted side by side
- ✓ Integrated UPS for targeted shutdown of the application
- ✓ Configuration via USB
- ✓ Web server HTML5 and JAVA
- ✓ SD card up to 2 GB as optional plug-in parameterization memory
- ✓ 2 x Ethernet interfaces (integrated switch)
- ✓ Increased resistance to EMI
- ✓ Extended temperature range of -25°C ... +60°C



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 731195
GTIN	4046356731195
Weight per Piece (excluding packing)	220.000 g

## Controller - AXC 1050 - 2700988

Custom tariff number	85371091
Country of origin	Germany

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

Width	45 mm
Height	125.9 mm
Depth	74 mm

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport)	5 % ... 95 % (according to DIN EN 61131-2)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above mean sea level)
Air pressure (storage/transport)	58 kPa ... 106 kPa (up to 4500 m above sea level)
Shock	30g, 11 ms period, half-sine shock pulse, according to IEC 60068-2-27
Vibration (operation)	5g

#### Control system

Programming tool	PC WORX / PC WORX EXPRESS
Diagnostics tool	DIAG+
Configuration tool	Config+ Version 1.01 or later

#### Mechanical design

Weight	225.6 g
Diagnostics display	No
Controller redundancy	No

#### Data interfaces

Interface	Axioline F local bus
Number	1
Connection method	Bus base module
Transmission speed	100 Mbps
Interface	Parameterization/operation/diagnostics
Number	1
Connection method	Micro USB type B
Transmission speed	max. 115.2 kbps

# Controller - AXC 1050 - 2700988

## Technical data

### Data interfaces

Interface	Ethernet
Number	2
Connection method	RJ45 socket
Transmission speed	10/100 Mbps

### PROFINET

Device function	PROFINET controller, PROFINET device
Specification	Version 2.2
Update rate	min. 4 ms

### Power supply

Typical current consumption	125 mA
Max. current consumption	160 mA
Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC
Residual ripple	± 5 %
Power dissipation	max. 3 W

### Fieldbus function

Amount of process data	max. 4096 Bit (Axioline F local bus (input))
	max. 4096 Bit (Axioline F local bus (output))
	max. 32768 Bit (internal Modbus /TCP client)
Number of supported devices	max. 63
Number of local bus devices that can be connected	max. 63 (observe current consumption)

### General data

Processor	Altera Nios II 100 MHz
-----------	------------------------

### IEC 61131 runtime system

Programming tool	PC WORX / PC WORX EXPRESS
Program memory	1 Mbyte
Mass storage	2 Mbyte
Retentive mass storage	48 kByte (NVRAM)
Number of control tasks	8
Realtime clock	Yes

### Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Developed in acc. with standard	Noise immunity test in accordance with EN 61000-6-2
Test result	Criterion B, 6 kV contact discharge, 8 kV air discharge
	Criterion A, Field intensity: 10 V/m

# Controller - AXC 1050 - 2700988

## Technical data

### Standards and Regulations

	Criterion B, 2 kV
	Criterion B, DC supply lines: $\pm 0.5$ kV/ $\pm 0.5$ kV (symmetrical/asymmetrical), fieldbus cable shield: $\pm 1$ kV
	Criterion A; Test voltage 10 V
	Class B
Vibration (storage/transport)	5g
Shock	30g, 11 ms period, half-sine shock pulse, according to IEC 60068-2-27
Vibration (operation)	5g
Shock (operation)	10g (Bump endurance test according to EN 60068-2-29)

### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Classifications

### eCl@ss

eCl@ss 4.0	27240602
eCl@ss 4.1	27240602
eCl@ss 5.0	27242589
eCl@ss 5.1	27242590
eCl@ss 6.0	27242590
eCl@ss 7.0	27242590
eCl@ss 8.0	27242207
eCl@ss 9.0	27242207

### ETIM

ETIM 3.0	EC001045
ETIM 4.0	EC001435
ETIM 5.0	EC000236
ETIM 6.0	EC000236

### UNSPSC

UNSPSC 6.01	81111810
UNSPSC 7.0901	81111810
UNSPSC 11	81111810
UNSPSC 12.01	81111810
UNSPSC 13.2	39122114

# Controller - AXC 1050 - 2700988

## Approvals

### Approvals

#### Approvals

UL Listed / cUL Listed / NK / EAC / DNV GL / BV / PRS / ABS / RINA / LR / BSH / cULus Listed

#### Ex Approvals

### Approval details

UL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 238705
-----------	--	---	---------------

cUL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 238705
------------	--	---	---------------

NK		<a href="http://www.classnk.or.jp/hp/en/">http://www.classnk.or.jp/hp/en/</a>	14A006
----	--	---	--------

EAC			EAC-Zulassung
-----	--	--	---------------

DNV GL		<a href="http://exchange.dnv.com/tari/">http://exchange.dnv.com/tari/</a>	TAA00000DF
--------	--	---	------------




BV		<a href="http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials">http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials</a>	36433/A2 BV
----	--	---	-------------

PRS		<a href="http://www.prs.pl/">http://www.prs.pl/</a>	TE/2106/880590/16
-----	--	---	-------------------

ABS		<a href="http://www.eagle.org/eagleExternalPortalWEB/">http://www.eagle.org/eagleExternalPortalWEB/</a>	17-HG1642658-PDA
-----	--	---	------------------

## Controller - AXC 1050 - 2700988

### Approvals

RINA		<a href="http://www.rina.org/en">http://www.rina.org/en</a>	ELE0078216XG
LR		<a href="http://www.lr.org/en">http://www.lr.org/en</a>	14-20019
BSH		<a href="http://www.bsh.de/de/index.jsp">http://www.bsh.de/de/index.jsp</a>	840
cULus Listed			

### Accessories

#### Accessories

#### Drivers and interfaces

#### Software - AX OPC SERVER - 2985945



AX OPC SERVER, communication interface for OPC-capable visualization with PC WORX-based controls.

---

#### Software - PC WORX UA SERVER-PLC 10 - 2402684



OPC UA server for communication with a maximum of 10 modular small-scale controllers (AXC 1xxx or ILC 1x1)

---

#### Software - PC WORX UA SERVER-PLC 40 - 2402685



OPC UA server for communication with a maximum of 25 controllers

## Controller - AXC 1050 - 2700988

### Accessories

---

Software - PC WORX UA SERVER-PLC 80 - 2402686



OPC UA server for communication with a maximum of 200 controllers

---

### Parameterization memory

Memory - SD FLASH 512MB - 2988146



Program and configuration memory, plug-in, 512 Mbyte.

---

Program / configuration memory - SD FLASH 512MB APPLIC A - 2701799



Program and configuration memory, plug-in, 512 MB with license key for functional block libraries, e.g., for: SNMP, SQL, wireless, motion functions, etc.

---

Memory - SD FLASH 512MB PDPI BASIC - 2701800



Program and configuration memory, plug-in, 512 MB with license key for licensing the PDPI - BASIC functional block for precise multi-channel controllers with self-optimization, e.g., for heating and cooling functions or hydraulic movements.

---

Memory - SD FLASH 512MB PDPI PRO - 2701801



Program and configuration memory, plug-in, 512 MB with license key for licensing the PDPI - PRO functional block for precise multi-channel controllers with self-optimization, additional functions: e.g., for setpoint processing, for heating and cooling functions.

---

## Controller - AXC 1050 - 2700988

### Accessories

Program / configuration memory - SD FLASH 2GB - 2988162



Program and configuration memory

---

Program / configuration memory - SD FLASH 2GB APPLIC A - 2701190



Program and configuration memory, plug-in, 2 Gbytes with license key for function block libraries, e.g., for: SNMP, SQL, wireless, motion functions, etc.

---

Program / configuration memory - SD FLASH 2GB AXC EASY SAFE PRO - 2403730



Program and configuration memory, plug-in, 2 GB, with license key and application program for easy web-based configuration and startup of a SafetyBridge solution including communication via Modbus/TCP, PROFINET, and e-mail.

---

Program / configuration memory - SD FLASH 2GB 61850 - 2400435



Program and configuration memory, plug-in, 2 GB with license key for IEC 61850 communication

---

Program / configuration memory - SD FLASH 2GB APPLIC A 61850 - 2400436



Program and configuration memory, plug-in, 2 GB with license key for IEC 61850 communication and for function block libraries, e.g., SNMP, SQL, wireless, motion functions, etc.

---



## Controller - AXC 1050 - 2700988

### Accessories

Program / configuration memory - SD FLASH 2GB ATWISE - 2400088



Program and configuration memory, plug-in, 2 GB with license key for webMI from atwise®

---

Program / configuration memory - SD FLASH 2GB APPLIC A ATWISE - 2400089



Program and configuration memory, plug-in, 2 GB with license key for function block libraries, e.g., for: webMI from atwise®, SNMP, SQL, wireless, motion functions, etc.

---

### Programming

Software - PC WORX DEMO - 2985725



Software package for PC-based automation solutions, PC WORX DEMO, contains all 5 IEC languages, with MSFC compiler, max. 16 bytes input and output data

---

Software - PC WORX BASIC LIC - 2985275



Software package for PC-based automation solutions, PC WORX BASIC license, contains all 5 IEC languages, without MSFC compiler, max. 2048 byte input and output data, version-specific license key

---

Software - PC WORX PRO LIC - 2985385



Software package for PC-based automation solutions, PC WORX PRO license, contains all 5 IEC languages, with MSFC compiler, max 128 kB input and output data, version-specific license key

---

## Controller - AXC 1050 - 2700988

### Accessories

#### Programming cable

Connecting cable - CAB-USB A/MICRO USB B/2,0M - 2701626



Connecting cable, for connecting the controller to a PC for PC Worx and LOGIC+, USB A to micro USB B, 2 m in length.

---

#### Spare parts

Bus connector - AXL BS BK - 2701422



Axioline F bus base module for housing type BK

---

Plug - AXL CN S/UL - 2701421



Axioline F short power connector (for e.g., AXL F BK ...)

---