2261 (5561) Series



RoHS **Compliant**



Specifications:


Current Rating : 5.0A AC/DC Voltage Rating : 250V AC/DC Max. Contact Resistance : 10mΩ. Min. Insulation Resistance : 1,000M Ω .

Withstanding Voltage : 1,500V AC for one minute.


Operating Temperature Range : -25°C to +105°C

Material and Finish:

Wafer Insulator : Nylon 46(UL94V-2) Contact Pin : Copper Alloy Tin Plated




Recommended PCB layout



Dimensions: Millimetres

Part Number Explanation:



Type : S = Single Row and Straight Type. 02 = 2,03 = 3 and 04 = 4 Positions. Number of Positions

Part Number Table

Description	No. of Positions	Dim. A	Dim. B	Part Number
3mm Pitch Single Row Headers, Straight Type,Through Hole	2	3mm	9.65mm	2261(5561)SA-02
	3	6mm	12.65mm	2261(5561)SA-03
	4	9mm	15.65mm	2261(5561)SA-04

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

