




Left Side

Connector(s): LC-Duplex Secure
Mode: MM
Housing Color: Violet
Geom. Spec: N/A

Fiber Path


A - _____ - Fiber B
B - _____ - Fiber A

Notes:

2 Includes dust caps (not shown on print).

Right Side

Connector(s): MT-RJ (No Pins)
Mode: MM
Housing Color: Black
Geom. Spec: 115-1215



VIEW D-D
NOT TO SCALE

	A	Rev Per EC#	RELEASE	3/25/2010	-	JS			
P	LTR	REVISION RECORD	DATE	DATE	DATE	APVD			

DIMENSIONS:
meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 P.L.C. ± .
1 P.L.C. ± .
2 P.L.C. ± .
3 P.L.C. ± .
4 P.L.C. ± .

Restricted To:

DWG Cable Assy Configurator		MATERIAL	HEAT TREAT	
CHK	Jeff Shipe			
APVD	Jeff Shipe			
NAME FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex Secure to MT-RJ (No Pins)				
SCALE NTS	SIZE A2	DRAWING NO C- 1907120	SHEET 1 of 4	REV A

THIS DRAWING IS A CONTROLLED DOCUMENT

DWG NO

LOC
CE
DIST
16

CAC Customer Layout Rev: D

Part #	L (meters)	L (feet)	LC-Duplex Secure, Violet		MT-RJ (No Pins), Black	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
4-1907120-3	42.570 - 43.430	139.66 - 142.48	0.56	-	0.56	20
4-1907120-4	43.560 - 44.440	142.91 - 145.80	0.57	-	0.57	20
4-1907120-5	44.550 - 45.450	146.16 - 149.11	0.57	-	0.57	20
4-1907120-6	45.540 - 46.460	149.40 - 152.42	0.57	-	0.57	20
4-1907120-7	46.530 - 47.470	152.65 - 155.74	0.57	-	0.57	20
4-1907120-8	47.520 - 48.480	155.90 - 159.05	0.57	-	0.57	20
4-1907120-9	48.510 - 49.490	159.15 - 162.36	0.57	-	0.57	20
5-1907120-0	49.500 - 50.500	162.40 - 165.68	0.58	-	0.58	20
5-1907120-1	50.490 - 51.510	165.64 - 168.99	0.58	-	0.58	20
5-1907120-2	51.480 - 52.520	168.89 - 172.30	0.58	-	0.58	20
5-1907120-3	52.470 - 53.530	172.14 - 175.62	0.58	-	0.58	20
5-1907120-4	53.460 - 54.540	175.39 - 178.93	0.58	-	0.58	20
5-1907120-5	54.450 - 55.550	178.64 - 182.25	0.58	-	0.58	20
5-1907120-6	55.440 - 56.560	181.88 - 185.56	0.58	-	0.58	20
5-1907120-7	56.430 - 57.570	185.13 - 188.87	0.59	-	0.59	20
5-1907120-8	57.420 - 58.580	188.38 - 192.19	0.59	-	0.59	20
5-1907120-9	58.410 - 59.590	191.63 - 195.50	0.59	-	0.59	20
6-1907120-0	59.400 - 60.600	194.88 - 198.81	0.59	-	0.59	20
6-1907120-1	60.390 - 61.610	198.12 - 202.13	0.59	-	0.59	20
6-1907120-2	61.380 - 62.620	201.37 - 205.44	0.59	-	0.59	20
6-1907120-3	62.370 - 63.630	204.62 - 208.75	0.59	-	0.59	20
6-1907120-4	63.360 - 64.640	207.87 - 212.07	0.6	-	0.6	20
6-1907120-5	64.350 - 65.650	211.12 - 215.38	0.6	-	0.6	20
6-1907120-6	65.340 - 66.660	214.37 - 218.70	0.6	-	0.6	20
6-1907120-7	66.330 - 67.670	217.61 - 222.01	0.6	-	0.6	20
6-1907120-8	67.320 - 68.680	220.86 - 225.32	0.6	-	0.6	20
6-1907120-9	68.310 - 69.690	224.11 - 228.64	0.6	-	0.6	20
7-1907120-0	69.300 - 70.700	227.36 - 231.95	0.61	-	0.61	20
7-1907120-1	70.290 - 71.710	230.61 - 235.26	0.61	-	0.61	20
7-1907120-2	71.280 - 72.720	233.85 - 238.58	0.61	-	0.61	20
7-1907120-3	72.270 - 73.730	237.10 - 241.89	0.61	-	0.61	20
7-1907120-4	73.260 - 74.740	240.35 - 245.20	0.61	-	0.61	20
7-1907120-5	74.250 - 75.750	243.60 - 248.52	0.61	-	0.61	20
7-1907120-6	75.240 - 76.760	246.85 - 251.83	0.61	-	0.61	20
7-1907120-7	76.230 - 77.770	250.09 - 255.15	0.62	-	0.62	20
7-1907120-8	77.220 - 78.780	253.34 - 258.46	0.62	-	0.62	20
7-1907120-9	78.210 - 79.790	256.59 - 261.77	0.62	-	0.62	20
8-1907120-0	79.200 - 80.800	259.84 - 265.09	0.62	-	0.62	20

	A	Rev Per EC# RELEASE	9/25/2010	-	J5
P	LTR	REVISION RECORD	DATE	DIN	AP

DIMENSIONS:		
meters		
		0
		1
		2
		3
		4

TOLERANCES UNLESS OTHERWISE SPECIFIED		
PLC	±	"
PLC	±	"
PLC	±	"
PLC	±	"
PLC	±	"

Restricted To:

Q1 Cable Assy Configurator		MATERIAL -		HEAT TREAT -	
CHK Jeff Shippe		 Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD Jeff Shippe					
NAME FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex Secure to MT-RJ (No Pins)					
SCALE NTS	SIZE A2	DRAWING NO C- 1907120	SHEET 3 of 4	REV A	

D

C

3

A

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT MAY NOT BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

THIS DRAWING IS A CONTROLLED DOCUMENT.

LOC
CE
DIST
16

CAC Customer Layout Rev: D

8 7 6 5 4 3 2 1

Label 1

Per specification 107-1645-1

Trace # - Bar Code

XXXXXXXXXXXXXXXX

Trace # - Human Readable

Logo

Made in XXXX

X-XXXXXXXX-X

Part Number

Country of Origin

This label is used on all lengths on this drawing.

	A	Rev Per EC#	RELEASE	3/25/2010	-	JS			
P	LTR	REVISION RECORD		DATE	DIN	APVD			

DIMENSIONS: meters	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 P.L.C. ± .
	1 P.L.C. ± .
	2 P.L.C. ± .
	3 P.L.C. ± .
	4 P.L.C. ± .

Restricted To:

DIN	Cable Assy Configurator		MATERIAL	HEAT TREAT
CHK	Jeff Shipe			
APVD	Jeff Shipe		AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 2 fiber, 50/125, OFNP (Plenum) jacket, LC-Duplex Secure to MT-RJ (No Pins)			
SCALE	NTS	SIZE	A2	DRAWING NO
				C- 1907120
SHEET	4 of 4	REV	A	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-1907120-2](#)