

Electronic housing - ME 45 UT/FE BUS/10+2 BU - 2706755

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Component housing with vents, Lower part, Cross connection: integrated bus connector, Color: blue, Width: 45 mm, Number of positions cross connector: 10+2

Why buy this product

- ▼ Tool-free mounting
- Available in overall widths from 12.5 mm to 90 mm, modular extension is possible
- ✓ Inflammability class V0 according to UL 94
- Variety of connection technologies
- Optional bus connector that is either integrated or mounted on the DIN rail



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
GTIN	4 017918 839055
GTIN	4017918839055
Weight per Piece (excluding packing)	87.540 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Housing type	Component housing
Housing material	PA 6.6



Electronic housing - ME 45 UT/FE BUS/10+2 BU - 2706755

Technical data

	ra

General	
Color	blue
Ambient conditions	
Ambient temperature (operation)	-40 °C (depending on power dissipation)
Dimensions	
Length	99 mm
Width	45 mm
Technical data	
Connection in acc. with standard	CUL
Nominal voltage U _N	300 V

Connection in acc. with standard	CUL
Nominal voltage U _N	300 V
Nominal current I _N	8 A
Indicator1	CUL1
Flammability rating according to UL 94	V0
Power dissipation without gap	8.2 W
Power dissipation with 20 mm gap	16.5 W
Number of positions	32
	8

Standards and Regulations

Connection in acc. with standard	CUL
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / UL Recognized / cULus Recognized

Ex Approvals

Approval details



Electronic housing - ME 45 UT/FE BUS/10+2 BU - 2706755

Approvals

	UL Recognized	<i>7</i> .1	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868
--	---------------	-------------	---	---------------

cUL Recognized	http://database.ul.com/cgi-bin/XYV/template/L	ISEXT/1FRAME/index.htm FILE E 60425
	В	D
Nominal current IN	8 A	8 A
Nominal voltage UN	300 V	300 V

UL Recognized	http://database.ul.com/cgi-bin/XYV/template/L	ISEXT/1FRAME/index.htm	FILE E 60425
	В	D	
Nominal current IN	8 A	8 A	
Nominal voltage UN	300 V	300 V	

cULus Recognized

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com