



## BARRIER STRIPS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

### TE CONNECTIVITY (TE) 20P.374" DR BARRIER STRIP

[Buchanan](#) | .374 DBL Row

2-1546306-0  
TE Internal Number: 2-1546306-0

Always EU RoHS/ELV Compliant

Barrier Style **Dual Barrier**

Bottom Termination Style **Quick Connects**

Current Rating (A) **20**

Centerline **9.53 mm [ .375 in ]**

Number of Positions **20**

#### Product Drawings

[9.50MM \(.374\) DBL ROW BARRIER STRIP W/O WASHER](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_GS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[1-1773458-2\\_BARRIER\\_STRIPS\\_QUICK\\_REFERENCE\\_GUIDE](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

#### Product Type Features

Block Style

**Flat**

Product Type

**Barrier Strip**

Applies To

**Printed Circuit Board**

#### Configuration Features

Number of Positions

**20**

Number of Rows

**2**










	Number of Rows	-
	Number of Levels	1
Electrical Characteristics	Current Rating (A)	20
	Voltage (V)	300
	Current Rating (Max) (A)	20
Body Features	Barrier Style	Dual Barrier
	Color	Black
Contact Features	Terminal Material	Brass
	Terminal Plating Material	Tin
Termination Features	Bottom Termination Style	Quick Connects
Mechanical Attachment	Mounting Options	End Mounting Ears
	Screw Material	Steel
	Screw Plating Material	Nickel
	Mounting Insert	Without
	Mounting Angle	Vertical
	Mounting Style	Open End Position
	Mounting Ears	With
	Screw Size	6-32
Housing Features	Centerline	9.53 mm [ .375 in ]
	Housing Material	Thermoplastic
Dimensions	Wire Range	22 – 12 AWG [ .3 – 3 mm <sup>2</sup> ]
	Length	207 mm [ 8.15 in ]
Usage Conditions	Operating Temperature Range	-40 – 120 °C [ -40 – 248 °F ]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	50
	Packaging Method	Carton

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

BARRIER STRIPS	CRIMP RINGS & SPADES	RECTANGULAR POWER CONNECTORS	BREAKOUTS/TRANSITIONS
 <b>30P.374" DR BARRIER STRIP</b> 3-1546306-0	<b>SOLIS SPDFLG 22-16COM22-18MIL6</b> 323136	<b>01P .062 COMM P&amp;S PLUG</b> 770278-1	<b>382A023-4/86-0</b> 382A023-4/86-0
 Save to List  Find Similar Products	 Save to List  Find Similar Products	 Save to List  Find Similar Products	 Save to List  Find Similar Products