

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_MMCX-50-0-1/111_O

Rev.: B



Description

Straight bulkhead receptacle jack

Interface standards
SUHNER-MMCX



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Weight 0.0008 kg

Environmental Data

Operating Temperature -55 °C to 155 °C

Material Data

Piece Parts

| Piece Parts | Material |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PFA / PTFE |
| Fastening nut | Brass |
| Washer | Bronze |

Surface Plating

| |
|-----------------------------------|
| Gold Plating (Nickel underplated) |
| Gold Plating |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00010459 |
| Catalogue drawing | DCA-00010461 |
| Mounting hole | DOU-00009144 |

Ordering Information

| | |
|----------------------|-----------------------|
| Bulk 100 pcs package | 22_MMCX-50-0-1/111_OH |
| Single package | 22_MMCX-50-0-1/111_OE |

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions