


DESCRIPTION: 2mm DUAL HEADER STRIP STRAIGHT

MATERIALS:

HOUSING: NYLON 6T - UL 94V-0
 COLOR: BLACK
 CONTACTS: COPPER ALLOY
 PLATING: GOLD FLASH ENTIRE CONTACT
 RoHS COMPLAINT

CURRENT RATING: 1 AMP
 INSULATOR RESISTANCE: 5000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING: 500V AC
 OPERATING TEMP: -40°C TO +105°C
 MAX PROCESSING TEMP: 260°C FOR
 10 SECONDS

"L" = NO. OF PINS/ROW X .079 - .079




2664 YY 01RP2

SERIES _____
 2664 = DUAL ROW

POSITIONS _____
 DUAL = INCREMENTS OF 2
 (2 TO 72)

TYPE _____
 01 = STRAIGHT

PLATING _____
 P2 = GOLD FLASH ENTIRE CONTACT

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.		DRAWN: PAM JENKINS	DATE: 1-27-06
	<h1>NorComp</h1>		CHECKED:	DATE:
SCALE:			SHEET 1 OF 1	REV 2
DWG NO.			2664YY01RP2	