



CRIMP RINGS & SPADES



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

PG R 22-16 COMM 22-18 MIL 10

[PLASTI-GRIP](#) | [PLASTI-GRIP](#)

2-32952-1

TE Internal Number: 2-32952-1

[Always EU RoHS/ELV Compliant](#)

Terminal Shape **Ring Tongue**

Stud Diameter (mm) **4.82, 10**

Stud Diameter (in) **.394**

Tongue Thickness **.84 mm [.033 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

[TERMINAL, RING TONGUE, PLASTI-GRIP, WIRE SIZE, 22-16 AWG](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Product Specifications

Application Specification

[PLASTI-GRIP Terminals And Splices](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-32952-1_03012016838_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealed

No

Barrel Type


Closed Barrel

	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Stud Size	10
	Shape Code	RING-043
	Wire/Cable Composition	Solid or Stranded
Configuration Features	Number of Holes	1
Electrical Characteristics	Voltage (Max) (V)	600
Body Features	Plating Material	Copper, Tin
	Insulation Sleeve Material	PVC
	Insulation Sleeve Color	Red
	Insulation Material	Vinyl
	Inspection Slot	No
	Weight per Piece (g)	1.903
	Insulation Type	Pre-Insulated
Contact Features	Terminal Shape	Ring Tongue
	Terminal Orientation	Straight
Dimensions	Stud Diameter (mm)	4.82, 10
	Stud Diameter (in)	.394
	Tongue Thickness	.84 mm [.033 in]
	Wire Insulation Diameter (Max)	3.18 mm [.125 in]
	Wire Insulation Diameter	2.03 – 3.18 mm [.08 – .125 in]
	Wire Size (AWG)	22
	Wire Size (mm²)	.3 – 1.42
	Wire Size (CMA)	509 – 3260
	Material Thickness	.79 mm [.031 in]
	Overall Length	21.74 mm [.856 in]
Usage Conditions	Operating Temperature Range (°C)	105

Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Tape Mounted
	Packaging Quantity	5000
Other	Barrel Color	Red
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

CRIMP RINGS & SPADES




TERMINAL, PIDG R 16-14 5/16
2-320575-1

Save to List

Find Similar Products

CRIMP WIRE PINS & TABS



180 SHPL REC 18-14 016TPBR
61412-2

Save to List

Find Similar Products

MOTOR TERMINAL HOUSINGS

FF 250 TAB HSG 6P NYLON BLACK
1-480282-0

Save to List

Find Similar Products

RECTANGULAR CONTACT INSERTS

LA3S .248, .008, SILPL
2-192039-1

Save to List

Find Similar Products