



PCB D-SUB CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

V23529B1121C215=SUB D STIFTLI

AMPLIMITE | Standard

2-1393480-2

TE Internal Number: 2-1393480-2

Alias ID: V23529B1121C215

Always EU RoHS/ELV Compliant

Connector Style **Plug**

Centerline (mm) **2.74**

Number of Positions **15**

Number of Rows **2**

Shell Size **2**

Product Drawings

Mounting Height 3,6 Mm

PDF
English

CAD Files

3D PDF

PDF
3D

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

AMPLIMITE Subminiature D Connectors - Right-Angle Posted Connectors

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Plug

Shell Size

2

Profile

Eurostyle

PCB Mounting Orientation

Right Angle

Grounding Straps

Without

Shell Type

Full Metal Shell

Shell Type	Full Metal Shell
Footprint	9.43 mm [.371 in]
Grounding Indents	Without
Applies To	Printed Circuit Board
Sealed	No
Product Type	Connector

Configuration Features	Number of Positions	15
	Number of Rows	2
	Performance Level	Level 2
	Preloaded	Yes

Body Features	Plastic	No
	Color Code	None
	Shell Plating Material	Tin
	Color	Gray
	Shell Material	Steel

Contact Features	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Copper Alloy
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold

Termination Features	Termination Post Length	3.2 mm [.126 in]
	Grounding Clips	Without

Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Mounting Holes
	Mating Connector Lock	Without
	Panel Mount Retention	With
	Mounting Hole Diameter	3.1 mm [.12 in]

Housing Features	Centerline (mm)	2.74
	Housing Color	Gray
	Housing Material	Thermoplastic PBTP

Dimensions	PCB Thickness (Recommended)	1.6 mm [.063 in]
Industry Standards	Approved Standards	DIN 41652
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Box
	Packaging Quantity	100
Other	Installation Height (mm)	3.6
Product Compliance	Statement of Compliance PDF	VIEW ALL PRODUCT COMPLIANCE