




BOARD-TO-BOARD HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

2X25P HV100 REC CON. TE, 8.5MM

[AMPMODU](#) | [AMPMODU](#)

2-215309-5

TE Internal Number: 2-215309-5

[Always EU RoHS/ELV Compliant](#)

Connector Style **Receptacle**

Centerline **2.54 mm [.1 in]**

Number of Positions **25**

Contact Mating Area Plating Material **Gold**

Contact Mating Area Plating Thickness (µin) **30**

Product Drawings

[HV 100 VERTICAL CONNECTOR, DUAL ROW, 8.5mm HEIGHT, TOP ENTRY ,
GOLD, MAX. 2X36 POSITIONS](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Receptacle

PCB Mounting Orientation

Vertical

Row-to-Row Spacing

2.54 mm [.1 in]

Profile

Standard

Applies To

Printed Circuit Board

Product Type

Connector

Boss

Without

	Series	AMPMODU, HV-100
	Sealed	No
	Connector Type	Connector Assembly
Configuration Features	Number of Positions	25
	Number of Rows	2
	Stackable	Yes
Contact Features	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	30
	Contact Shape	Square
	Contact Current Rating (A)	3
	Contact Type	Socket
	Solder Tail Contact Plating Material	Tin
	Contact Layout	Inline
	Solder Tail Contact Plating Thickness	2.5 µm [98.425 µin]
	Contact Base Material	Phosphor Bronze
Termination Features	Termination Method to PC Board	Through Hole - Solder
	Termination Post Length	3.1 mm [.122 in]
Mechanical Attachment	PCB Mount Retention	With
	PCB Mount Retention Type	Retention Solder Tails
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Polyester - GF
	Housing Color	Green
	Housing Entry Style	Closed Bottom, Closed Entry, Top
Dimensions	Tail Length	3.1 mm [.122 in]
	Height	8.5 mm [.335 in]
	PCB Thickness (Recommended) (mm)	1.6
Usage Conditions	Operating Temperature Range (°C)	-55 – 105, -65 – 125
Operation/Application	Pick and Place Cover	Without
	Assembly Process Feature	Board Standoff

For Use With

Header Assembly

Industry Standards

UL Flammability Rating

UL 94V-0

MIL-C-55032

No

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)