

215614-1 Product Details

Have a Question?

Chat with a Product Information Specialist



215614-1

TE Internal Number: 215614-1

Active

View 3D PDF

Eurocard Type C

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector Assembly
- Connector Style = Receptacle
- Contact Type = Socket
- Type = Type C
- 2.54 mm Centerline

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Add to My Part List

Request Sample

Find Similar Products

Buy Product

Documentation & Additional Information

Product Drawings:

- [96 POS FEMALE CONN. ASS'Y WITH ACTION-PIN. FOR 2,4-3... \(PDF, English\)](#)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing \(DXF, Version N\)](#)
- [3D Model \(IGES, Version N\)](#)
- [3D Model \(STEP, Version N\)](#)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Recommended PC Board Hole Pattern](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Connector Type = Connector Assembly
- [PCB Mount Retention](#) = With
- [PCB Mount Angle](#) = Vertical
- [PCB Thickness \(Minimum\) \(mm \[in\]\)](#) = 2.39 - 3.20 [0.094 - 0.126]
- [Post Type](#) = Compliant Post
- [Size](#) = Standard
- [Make First / Break Last](#) = No
- [Bus Type](#) = FUTUREBUS, MULTIBUS (II), NUBUS, VMEbus, VXIBus
- [DIN Level](#) = I
- [Mounting Ears](#) = With
- Toolless (Flat Rock) = No
- Comment = Seating tool required.

Termination Related Features:

- [Termination Post Length \(mm \[in\]\)](#) = 17.00 [0.669]

Body Related Features:

- [Type](#) = Type C
- [Centerline \(mm \[in\]\)](#) = 2.54 [0.100]
- [Number of Rows](#) = 3
- [Number of Positions](#) = 96
- [Rows Loaded](#) = A, B, C
- [PCB Mount Retention Type](#) = ACTION PIN (Compliant) Posts
- [Contact Cross Section \(mm \[in\]\)](#) = 0.64 [.025] Sq.

Contact Related Features:

- Contact Type = Socket
- Contact Base Material = Phosphor Bronze

Housing Related Features:

- Connector Style = Receptacle
- Housing Material = Polyester GF
- UL Flammability Rating = UL 94V-0

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- [Flux-Tight Coating](#) = Without
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- [Applies To](#) = Printed Circuit Board
- [High Temperature Housing](#) = No

Other:

- Brand = AMP



Corporate Information

Who We Are

Investors

News Room

Supplier Portal

Careers

Quick Links

Check Distributor Inventory

Cross Reference

Find Documents & Drawings

Product Compliance Support Center

Site Map

Customer Support

Email or Chat with Us

Find a Phone Number

Search Knowledge Base

Manage Your Account

Sign up for our eNewsletter

Enter your email address

Follow Us On:



Visit Us On:

