




CRIMP RINGS & SPADES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

TERMINAL,PIDG R IR 22 10

PIDG

2-36153-3

TE Internal Number: 2-36153-3

Mil-Spec: M7928/1-15

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **5 mm [.197 in]**

Tongue Thickness **.79 mm [.031 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

[TERMINAL, RING TONGUE, I.R., PIDG WIRE SIZE, 22-16 AWG](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_GS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Application Specification

[Pre-Insulated Diamond Grip \(PIDG\) Terminals, Splices, And End Caps](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-36153-3_05022015439_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealed

No


Barrel Type

Closed Barrel

	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Restriction
	Stud Size	10
	Shape Code	RING-042
	Barrel Style	Standard
	Wire/Cable Composition	Stranded
Configuration Features	Terminal Angle	Straight
	Number of Holes	1
Electrical Characteristics	Voltage (Max) (V)	300
Body Features	Plating Material	Copper, Tin
	Plating Thickness	2.54 μm [100 μin]
	Insulation Sleeve Material	Nylon
	Insulation Material	Nylon
	Inspection Slot	No
	Weight per Piece (g)	.83
	Stripe Color	Green
	Insulation Type	Pre-Insulated
Contact Features	Terminal Shape	Ring Tongue
	Terminal Orientation	Straight
	Class	1 & 2
Dimensions	Stud Diameter	5 mm [.197 in]
	Tongue Thickness	.79 mm [.031 in]
	Wire Insulation Diameter (Max)	2.79 mm [.11 in]
	Wire Insulation Diameter	.97 – 2.79 mm [.038 – .11 in]
	Wire Size (AWG)	22
	Wire Size (mm ²)	.3 – .4
	Wire Size (CMA)	754
	Barrel Inside Diameter (in)	.128
	Material Thickness	.79 mm [.031 in]

	Overall Length	23.01 mm [.91 in]
	Barrel Inside Diameter (Min) (in)	.128
Usage Conditions	Operating Temperature Range (°C)	105
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	Yes
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	1000
Other	Barrel Color	Red
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

DIP & SIP SWITCHES	AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD TERMINALS	RADIAL-LEADED DEVICES	HEAT SHRINK BOOTS
 <p>ADE0404=DIP SWITCH, EXT, THRU/HL 1825057-3</p> <p>Save to List Find Similar Products</p>	<p>PIN, SOLID, SIZE 16, 14AWG, NICKEL 0460-215-16141</p> <p>Save to List Find Similar Products</p>	<p>RGEF700 RGEF700</p> <p>Save to List Find Similar Products</p>	<p>222A142-25/225-0 222A142-25/225-0</p> <p>Save to List Find Similar Products</p>