




CRIMP RINGS & SPADES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE) TERMINAL,PIDG R 16-14 10 PIDG

2-320574-2
 TE Internal Number: 2-320574-2
 Alias ID: 1180732

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **4.82 mm [.19 in]**

Tongue Thickness **.84 mm [.033 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

[WIRE TERMINAL P.I.D.G RING TONGUE WIRE SIZE: 16-14](#)

PDF
 English

CAD Files

[3D PDF](#)

PDF
 English

[Customer View Model](#)

2D_DXF.ZIP
 English

[Customer View Model](#)

3D_IGS.ZIP
 English

[Customer View Model](#)

3D_STP.ZIP
 English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealed	No
Barrel Type	Closed Barrel
Wire/Cable Type	Regular Wire
Insulated	Yes
Insulated Wire Support	Yes
Support Style	Insulation Support
Stud Size	10
Shape Code	RING-041

	Barrel Style	Standard
	Wire/Cable Composition	Solid or Stranded
Configuration Features	Number of Holes	1
Electrical Characteristics	Voltage (Max) (V)	300
Body Features	Plating Material	Copper, Tin
	Insulation Material	Nylon
	Weight per Piece (g)	1.016
	Insulation Type	Pre-Insulated
Contact Features	Terminal Shape	Ring Tongue
	Terminal Orientation	Straight
Dimensions	Stud Diameter	4.82 mm [.19 in]
	Tongue Thickness	.84 mm [.033 in]
	Wire Insulation Diameter (Max)	3.81 mm [.15 in]
	Wire Insulation Diameter (mm)	2.68 – 3.81
	Wire Size (AWG)	16 – 14
	Wire Size (mm ²)	1.25 – 2
	Wire Size (CMA)	2050 – 5180
	Overall Length (mm)	21.62
	Barrel Inside Diameter (Min) (in)	.153
Usage Conditions	Operating Temperature Range (°C)	105
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Tape Mounted
	Packaging Quantity	5000
Other	Barrel Color	Blue

Product Compliance

Statement of Compliance
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)