



- △ THIS PLUG WILL MATE WITH ANY RECEPTACLE CONNECTOR WITH THE SAME INSERT ARRANGEMENT AS DEFINED BY MS18275-1.
- 2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS PLUG IS .072 DIA.
- 3. BERYLLIUM COPPER RETENTION CLIPS (37) ARE INCLUDED IN INSERT ASSEMBLY.
- 4. CONNECTOR SUPPLIED WITHOUT CONTACTS; SHOWN FOR ILLUSTRATION ONLY.
- △ FAR SIDE REFERS TO WIDE SIDE OF KEYSTONE.
- △ THESE CONNECTORS ARE QUALIFIED TO GODDARD SPACE FLIGHT CENTER SPECIFICATION S-311P-4.
- △ UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
- △ RESTRICTED TO CAE ELECTRONICS ONLY.

OBSOLETE	△	.120	570513-9	206802-6	206802-6
	△	.120	311P409-4P-B-12	206802-2	206802-5
			122137P37P	206802-4	206802-4
		.154	-	206802-3	206802-3
	△	.120	311P409-4P-B-12	206802-2	206802-2
	.154	311P409-4P-B-15	206802-1	206802-1	

REMARKS DIA A MARKED CUSTOMER P/N MARKED AMP P/N TE P/N

THIS DRAWING IS A CONTROLLED DOCUMENT.		REV	12-3-88	TE Connectivity	
DESIGNER	APPROVED	DATE	1-28-88	PLUG FOR PIN CONTACTS	
ENGINEER	DATE	1-28-88	SIZE 4, (37 POSITION)		
DATE	1-28-88	A1 00779 206802			
DATE	1-28-88	CUSTOMER DRAWING			