




High Frequency, High Current Power Inductors



- Excellent Q factors – up to 230 at 400 MHz!
- Current handling as high as 57 Amps
- Inductance values from 22 to 257 nH

Environmental RoHS compliant, halogen free

Terminations RoHS compliant tin-silver over copper

Ambient temperature –40°C to +125°C with Irms current, +125°C to +145°C with derated current

Storage temperature Component: –40°C to +145°C.
Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Temperature Coefficient of Inductance (TCL) +5 to +70 ppm/°C

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Mean Time Between Failures (MTBF) 1 billion hours

PCB washing Tested with pure water or alcohol only. For other solvents, see Doc787_PCB_Washing.pdf.

Part number ¹	Inductance ² ±20% (nH)	Q ³ typ	Q test freq (MHz)	SRF typ ⁴ (MHz)	DCR (mOhm)		Irms (A) ⁵		Weight (g)
					typ	max	20°C rise	40°C rise	
1010VS-23NME_	23.5	95	100	923	1.05	1.20	18.0	26.0	0.49
1010VS-46NME_	46.5	150	100	526	1.50	1.62	17.9	25.5	0.65
1010VS-79NME_	79.0	135	50	386	1.95	2.11	17.8	25.0	0.82
1010VS-111ME_	111	150	50	382	2.53	2.73	15.7	22.0	0.98
1010VS-141ME_	146	140	50	433	3.08	3.33	14.1	19.3	1.23
1212VS-22NME_	22.0	200	100	918	0.48	0.55	40.5	57.0	2.20
1212VS-42NME_	42.0	195	50	557	0.70	0.77	38.0	52.0	2.70
1212VS-66NME_	66.0	200	50	480	0.90	0.99	35.0	48.0	3.20
1212VS-90NME_	90.0	175	50	444	1.10	1.21	33.0	45.0	3.70
1212VS-111ME_	117	165	50	399	1.30	1.43	32.0	44.0	4.20
2014VS-33NME_	33	230	100	620	0.63	0.74	32.5	43.0	1.60
2014VS-66NME_	66	200	50	413	0.90	1.00	31.5	42.5	2.30
2014VS-111ME_	108	210	50	320	1.20	1.34	31.0	42.0	3.10
2014VS-151ME_	155	205	50	296	1.44	1.60	29.4	39.7	3.60
2014VS-201ME_	202	200	50	262	1.70	1.82	26.3	35.8	4.40
2014VS-251ME_	257	200	50	230	1.94	2.15	24.9	34.5	5.00

1. When ordering, please specify **packaging** code:

2014VS-251MEC

Packaging: C = 7" machine-ready reel (Standard for 1010VS.)
EIA-481 embossed plastic tape.
D = 13" machine-ready reel (Standard for 1212VS and
2014VS; optional, factory order only, not stocked for
1010VS.) EIA-481 embossed plastic tape.
B = Less than full reel. In tape, but not machine ready.
To have a leader and trailer added (\$25 charge), use
code letter C for 1010VS; D for 1212VS and 2014VS
instead.

- Inductance measured at 1.0 MHz, 0.1 Vrms, 0 A using an Agilent/HP HP4291A impedance analyzer with an Agilent/HP 16193A test fixture or equivalents.
 - Q measured at the specified frequency using an Agilent/HP 4291A impedance analyzer or equivalent.
 - SRF measured using an Agilent/HP 8753 network analyzer or equivalent and a Coilcraft CCF1199 test fixture
 - Current that causes the specified temperature rise from 25°C ambient.
 - Electrical specifications at 25°C.
- Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 893-1 Revised 08/08/14


© Coilcraft Inc. 2014

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.








High Frequency, High Current Power Inductors – 1010VS, 1212VS, 2014VS

L vs Frequency



Q vs Frequency



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 893-2 Revised 08/08/14




© Coilcraft Inc. 2014

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.






High Frequency, High Current Power Inductors – 1010VS, 1212VS, 2014VS

1010VS



Part number	Height		Weight (g)
	inches	mm	
1010VS-23N	0.142	3.60	0.49
1010VS-46N	0.161	4.10	0.65
1010VS-79N	0.189	4.80	0.82
1010VS-111	0.220	5.60	0.98
1010VS-141	0.240	6.10	1.23



1212VS




Part number	Height		Weight (g)
	inches	mm	
1212VS-22N	0.260	6.60	2.2
1212VS-42N	0.299	7.60	2.7
1212VS-66N	0.346	8.80	3.2
1212VS-90N	0.409	10.4	3.7
1212VS-111	0.445	11.3	4.2

All dimensions are in $\frac{\text{inches}}{\text{mm}}$.

2014VS



Part number	Height		Weight (g)
	inches	mm	
2014VS-33N	0.236	5.99	1.6
2014VS-66N	0.279	7.09	2.3
2014VS-111	0.327	8.31	3.1
2014VS-151	0.362	9.19	3.6
2014VS-201	0.409	10.4	4.4
2014VS-251	0.449	11.4	5.0



Packaging

1010VS-23N 250/7" reel ; 1000/13" reel; 3.81 mm pocket depth

1010VS-46N 250/7" reel ; 900/13" reel; 4.32 mm pocket depth

1010VS-79N 200/7" reel ; 800/13" reel; 5.05 mm pocket depth

Plastic tape: 24 mm wide, 0.35 mm thick, 16 mm pocket spacing

1010VS-111 175/7" reel ; 700/13" reel; 5.84 mm pocket depth

1010VS-141 150/7" reel ; 600/13" reel; 6.35 mm pocket depth

Plastic tape: 24 mm wide, 0.40 mm thick, 16 mm pocket spacing

1212VS-22N 450/13" reel; 8.86 mm pocket depth

1212VS-42N 400/13" reel; 7.87 mm pocket depth

1212VS-66N 350/13" reel; 9.02 mm pocket depth

1212VS-90N 300/13" reel; 10.67 mm pocket depth

1212VS-111 250/13" reel; 11.68 mm pocket depth

Plastic tape: 24 mm wide, 0.50 mm thick, 20 mm pocket spacing

2014VS-33N 500/13" reel; 6.22 mm pocket depth

2014VS-66N 450/13" reel; 7.37 mm pocket depth

2014VS-111 400/13" reel; 8.56 mm pocket depth

2014VS-151 350/13" reel; 9.45 mm pocket depth

2014VS-201 350/13" reel; 10.67 mm pocket depth

2014VS-251 250/13" reel; 11.68 mm pocket depth

Plastic tape: 44 mm wide, 0.50 mm thick, 20 mm pocket spacing



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com

UK +44-1236-730595 sales@coilcraft-europe.com

Taiwan +886-2-2264 3646 sales@coilcraft.com.tw

China +86-21-6218 8074 sales@coilcraft.com.cn

Singapore +65-6484 8412 sales@coilcraft.com.sg

Document 893-3 Revised 08/08/14

© Coilcraft Inc. 2014

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Coilcraft:

<u>1212VS-111MEB</u>	<u>1010VS-111MEB</u>	<u>2014VS-111MEB</u>	<u>1212VS-111MED</u>	<u>1212VS-66NMED</u>	<u>1010VS-46NMEC</u>
<u>2014VS-251MEB</u>	<u>2014VS-251MED</u>	<u>1212VS-66NMEB</u>	<u>1010VS-111MEC</u>	<u>2014VS-111MED</u>	<u>1010VS-23NMEB</u>
<u>2014VS-151MEB</u>	<u>2014VS-66NMED</u>	<u>1010VS-23NMEC</u>	<u>2014VS-66NMEB</u>	<u>1212VS-22NMED</u>	<u>1010VS-46NMEB</u>
<u>1212VS-22NMEB</u>	<u>1010VS-79NMEC</u>	<u>2014VS-201MED</u>	<u>1212VS-42NMED</u>	<u>1010VS-141MEB</u>	<u>1212VS-42NMEB</u>
<u>2014VS-33NMEB</u>	<u>1212VS-90NMEB</u>	<u>2014VS-151MED</u>	<u>2014VS-201MEB</u>	<u>1010VS-141MEC</u>	<u>1010VS-79NMEB</u>
<u>1212VS-90NMED</u>	<u>2014VS-33NMED</u>				