



CRIMP RINGS & SPADES



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE)

TERMINAL,PG SPD 16-14 8

PLASTI-GRIP

2-326741-1

TE Internal Number: 2-326741-1

Always EU RoHS/ELV Compliant

Terminal Shape **Spade Tongue**

Stud Diameter **4.34 mm [.171 in]**

Tongue Thickness **.79 mm [.031 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

[TERMINAL, SPADE, PLASTI-GRIP, WIRE SIZE: 16-14](#)

PDF (TIFF AVAILABLE)
English

[TERMINAL, SPADE, PLASTI-GRIP, WIRE SIZE: 16-14](#)

PDF (TIFF AVAILABLE)
English

Product Specifications

Application Specification

[PLASTI-GRIP Terminals And Splices](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealed

No

Barrel Type

Closed Barrel

Wire/Cable Type

Regular Wire

Insulated

Yes

Insulated Wire Support

Yes

Support Style

Insulation Support

Stud Size

8, M4

Shape Code

SPADE-021

Wire/Cable Composition

Solid or Stranded

Configuration Features

Terminal Angle

Straight

Electrical Characteristics	Voltage (Max) (V)	600
Body Features	Plating Material	Copper, Tin
	Insulation Sleeve Material	PVC
	Insulation Sleeve Color	Blue
	Insulation Material	Vinyl
	Inspection Slot	No
	Weight per Piece (g)	.247
Contact Features	Terminal Shape	Spade Tongue
	Terminal Orientation	Straight
Dimensions	Stud Diameter	4.34 mm [.171 in]
	Tongue Thickness	.79 mm [.031 in]
	Wire Insulation Diameter (Max)	4.9 mm [.193 in]
	Wire Insulation Diameter	3 – 4.9 mm [.118 – .193 in]
	Wire Size (AWG)	16 – 14
	Wire Size (mm²)	1.04 – 2.62
	Wire Size (CMA)	2050 – 5180
	Overall Length (mm)	19.43
	Barrel Inside Diameter (Min)	4.95 mm [.195 in]
Usage Conditions	Operating Temperature Range (°C)	105
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Tape Mounted
	Packaging Quantity	5000
Other	Barrel Color	Blue

