



RIBBON CABLE CONNECTORS



TE CONNECTIVITY (TE)

IDC LOW PRO HDR 14P VERT LG LA

AMP-LATCH | [Low Profile Headers](#)

2-1761606-5

TE Internal Number: 2-1761606-5

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

PCB Mount Retention **Without**

PCB Mounting Orientation **Vertical**

Termination Method to PC Board **Through Hole**

Shrouded **Yes**

Active

[PRODUCT DRAWING](#)
English

[3D PDF](#)

Product Drawings

[HEADER ASSEMBLY, VERTICAL, LONG EJECT LATCH, LOW PROFILE, IDC](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

Product Specifications

Product Specification

[AMP-LATCH And IDC Header Connectors, .100 X .100 Inch Grid](#)

PDF
English

Qualification Test Report

[Connector, AMP-LATCH Header, .100 X .100 Inch Grid](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

PCB Mounting Orientation

Vertical

Shrouded

Yes

Row-to-Row Spacing

2.54 mm [.1 in]

	Connector Style	Plug
	Profile	Low
	Applies To	Printed Circuit Board
	Product Type	Connector
	Board Standoff	Without
	Connector Type	Header
	Connector System	Wire-to-Board
	Ejection Latches	With
Configuration Features	Number of Positions	14
	Number of Rows	2
Electrical Characteristics	Operating Voltage (VAC)	250
	Insulation Resistance (MΩ)	1000 – 5000
Body Features	Post Size	.64 mm [.025 in]
	Header Type	Pin Header
	Daisy Chain	With
Contact Features	Contact Mating Area Plating Material	Gold Flash over Palladium Nickel
	Contact Mating Area Plating Thickness	.762 μm [30 μin]
	Contact Shape	Square
	Contact Transmits (Typical)	Signal (Data)
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Current Rating (A)	1
	Contact Base Material	Phosphor Bronze
	Contact Type	Pin
	Contact Termination Area Plating Material	Tin
	Contact Termination Area Plating Thickness	2.54 μm [100 μin]
Termination Features	Termination Method to PC Board	Through Hole
	Termination Post Length	2.6 mm [.102 in]
Mechanical Attachment	PCB Mount Retention	Without
	Mating Alignment Type	Center
	Mating Connector Lock	Without
	Mating Alignment	With

Polarization	With
Panel Mount Retention	Without
Mating Retention	With
PCB Mount Alignment	Without

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Blue
	Housing Style	4-Sided
	Housing Entry Style	Top
	Housing Material	PBT

Dimensions	Height	9.19 mm [.36 in]
	Length	25.4 mm [1 in]
	Shrouded End Dimension	3.76 mm [.148 in]

Usage Conditions	Temperature Rating	High
	Operating Temperature Range (°C)	-65 – 105

Operation/Application	For Use With	AMP-Latch Receptacle
-----------------------	--------------	-----------------------------

Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------

Packaging Features	Packaging Method	Tube
	Packaging Quantity	20

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

THROUGH-HOLE RESISTORS	RIBBON CABLE CONNECTORS	RJ45 CONNECTORS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES
<p>SQM7 220R 5% (METAL FILM) SQMR7220RJ</p>	<p>IDC LOW PRO HDR 10P VERT BLUE 2-1761603-3</p>	<p>MJ ASSY, 2P, 8POS, R/A, PCB, CAT5 5406443-1</p>	<p>08 MODII HDR DRST B/A .100CL 103240-4</p>



Save to List Find Similar Products

Save to List Find Similar Products

Save to List Find Similar Products

Save to List Find Similar Products

Products - 11 Results

View All

Compare 0/10

Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
I AMP-LATCH - NOVO

**622-1430LF FEM SOCKET,
LEAD FREE - 1658527-5**

TE INTERNAL NUMBER: 1658527-5

Active


Always EU RoHS/ELV Compliant

Number of Positions **14**

Connector Style **Receptacle**



PRODUCT - MATING PRODUCTS



Connectors - Ribbon Connector Accessories
AMP-LATCH | AMP-LATCH - NOVO

**622-1431=FSKT IDC S 14
SR - 7-1437023-1**

TE INTERNAL NUMBER: 7-1437023-1
ALIAS ID: 622-1431

Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**

Number of Positions **14**




RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
I AMP-LATCH - NOVO

**609-1441LF FEM SOCKET,
LEAD FREE - 1658526-9**

TE INTERNAL NUMBER: 1658526-9

Active

Always EU RoHS/ELV Compliant

Number of Positions **14**

Connector Style **Receptacle**



RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
I AMP-LATCH - NOVO

636-1430LF=FEM SKT

Always EU RoHS/ELV Compliant

Number of Positions **14**






BLADE POL 1 - 1-1658528-2

TE INTERNAL NUMBER: 1-1658528-2

✓ Active

Number of Positions **14**

Connector Style **Receptacle**



PRODUCT - MATING PRODUCTS

Connectors - Ribbon Connector Accessories
AMP-LATCH | AMP-LATCH - NOVO

622-1431=FSKT IDC S 14 SR - 7-1437023-1

TE INTERNAL NUMBER: 7-1437023-1
ALIAS ID: 622-1431

✓ Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**

Number of Positions **14**

