

Inline function terminal - IB IL 24 TC-PAC - 2861360

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Inline thermistor terminal block, complete with accessories (connector and labeling field), 2-wire connection method

Why buy this product

- Connection for a thermistor
- Integrated switching output
- Maximum permissible load current: 500 mA
- Diagnostic and status indicators

Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 894306
GTIN	4017918894306
Weight per Piece (excluding packing)	88.760 g
Custom tariff number	85389091
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---------------------------------------------------------------------------

Dimensions

Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm

Inline function terminal - IB IL 24 TC-PAC - 2861360

Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	-25 % ... 55 % (75% average, 85% seldom)
Permissible humidity (storage/transport)	-25 % ... 85 %
Air pressure (operation)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection	IP20

General

Mounting type	DIN rail
Net weight	50 g
Note on weight specifications	Without plug

Interfaces

Designation	Inline local bus
Connection method	Inline data jumper
Transmission speed	500 kbps
Transmission physics	Copper

Inline potentials

Communications power U_L	7.5 V DC
Current consumption from U_L	max. 60 mA
Segment circuit supply U_S	24 V DC
Current consumption from U_S	max. 500 mA
I/O supply voltage U_{ANA}	24 V DC
Current consumption from U_{ANA}	0 A DC
	0 A DC
Power consumption	max. 12 W (For $R = 12 \Omega$, $L = 1.2 \text{ H}/48 \Omega$)

Analog inputs

Number of inputs	1
Input name	Resistance sensor
Description of the input	Input for PTC thermistor
Connection method	Spring-cage connection
Connection technology	2-wire
Sensor types (RTD) that can be used	PTC thermistor according to DIN 44081 or DIN 44082
Linear resistance measuring range	2.7 k Ω ... 3.5 k Ω (Shutdown range, total resistance)
	50 Ω ... 2.25 k Ω (Operating range, total resistance)
Nominal value of the current sources	max. 1.2 mA (For non-load voltage of < 8 V DC)

Inline function terminal - IB IL 24 TC-PAC - 2861360

Technical data

Analog inputs

Input filter time	typ. 10 ms
-------------------	------------

Analog outputs

Number of outputs	1
Connection method	Spring-cage connection
Connection technology	2-wire
Type of protection	Short-circuit and overload proof
Current output signal	500 mA (per output)
Voltage output signal	24 V DC ($U_S - 1 V$)
Load/output load voltage output	< 2.7 k Ω (Total resistance for output signal HIGH)

Electrical isolation

Test section	5 V supply, incoming remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	5 V supply, outgoing remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	7.5 V supply (bus logics)/24 V analog supply (analog I/O) 500 V AC 50 Hz 1 min.
	24 V analog supply (analog I/O) / functional earth ground 500 V AC 50 Hz 1 min.
	Thermistor / all other areas 1200 V AC 50 Hz 1 min.

Standards and Regulations

Protection class	III, IEC 61140, EN 61140, VDE 0140-1
------------------	--------------------------------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

Inline function terminal - IB IL 24 TC-PAC - 2861360

Approvals

EAC



EAC-Zulassung