



WIRING DIAGRAM
568A

LOC	DIST	REV	DESCRIPTION	DATE	DMN	APPD
EH	00	P				
		LTR				
N			ECR-12-021378	12DEC2012	CL	AZ

- ONE CABLE ASSEMBLY PACKAGED IN ONE POLYBAG.
- DIMENSIONS ARE MAXIMUM UNLESS OTHERWISE SPECIFIED.
- CABLE: CAT-5E UNSHIELDED 24 AWG, 4 TWISTED PAIRS, 7/32 STRANDED CONDUCTORS, 100 OHMS.
- DESIGNATIONS IN PARENTHESES () ARE FOR REFERENCE ONLY.
- CAT 5E PATCH CORD COMPONENT COMPLIANT.

0.15	0.5	203.2 (8.00)	9-219245-8
24.38	80	24536.4 (966.00)	8-219245-0
21.34	70	21488.4 (846.00)	7-219245-0
15.24	50	15392.4 (606.00)	5-219245-0
12.20	40	12344.4 (486.00)	4-219245-0
9.15	30	9296.4 (366.00)	3-219245-0
7.62	25	7721.6 (304.00)	2-219245-5
6.10	20	6197.6 (244.00)	2-219245-0
4.88	16	4978.4 (196.00)	1-219245-6
4.57	15	4724.4 (184.00)	1-219245-5
4.27	14	4368.8 (172.00)	1-219245-4
3.66	12	3759.2 (148.00)	1-219245-2
3.05	10	3149.6 (124.00)	1-219245-0
2.74	9	2794 (110.00)	219245-9
2.44	8	2489.2 (98.00)	219245-8
2.14	7	2184.4 (86.00)	219245-7
1.83	6	1879.6 (74.00)	219245-6
1.53	5	1574.8 (62.00)	219245-5
1.22	4	1270 (50.00)	219245-4
0.92	3	965.2 (38.00)	219245-3
0.61	2	660.4 (26.00)	219245-2
0.30	1	355.6 (14.00)	219245-1

219245

THIS DRAWING IS A CONTROLLED DOCUMENT.

DMN	M. BOLES	25JUL97	
CHK	B. ANTHONY	25JUL97	
APPD	B. ANTHONY	25JUL97	

DIMENSIONS: mm [INCHES]
 TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 PIC ±
 2 PIC ±
 3 PIC ±
 4 PIC ±
 ANGLES ±
 FINISH -

MATERIAL:

DIM A: 2
 DIM A: 2

CUSTOMER DRAWING: A2 00779 C-219245

SCALE: NTS SHEET: 1 OF 1 REV: N

STE TE Connectivity
 CABLE ASSEMBLY, MOD PLUG, 8 POSITION
 WHITE, ENHANCED CATEGORY 5