

Type 3 surge protection base element - PLT-SEC-T3-BE - 2905557

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Base element for protective plugs from the PLUGTRAB SEC product series with remote indication contact.



Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4046356961967

Technical data

Dimensions

Height	90 mm
Width	17.7 mm
Depth	51.2 mm (incl. DIN rail 7.5 mm)
Horizontal pitch	1 Div.

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl (above mean sea level))
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	30g (Half-sine / 11 ms /3x, #X, #Y, #Z)
Vibration (operation)	5g (10 ... 150 Hz/20 cycles/axis/X, Y, Z)

General

IEC test classification	III
	T3
EN type	T3
Number of ports	One

Type 3 surge protection base element - PLT-SEC-T3-BE - 2905557

Technical data

General

Mounting type	DIN rail: 35 mm
Color	traffic grey A RAL 7042
Housing material	PA 6.6-FR
Degree of pollution	2
Flammability rating according to UL 94	V-0
Type	Base element, DIN rail mounting
Number of positions	2
Surge protection fault message	Remote indication contact

Protective circuit

Nominal voltage U_N	230 V AC (TN-S)
	230 V AC (TT)
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous voltage U_C	264 V AC
Rated load current I_L	26 A (30 °C)
Short-circuit current rating I_{SCCR}	1.5 kA AC
Max. backup fuse with branch wiring	not required
Maximum backup fuse for through wiring	25 A (gG / B / C)

Indicator/remote signaling

Switching function	N/C contact
Connection method	Screw connection
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 12
Screw thread	M3
Tightening torque	0.8 Nm
Stripping length	8 mm

Connection data

Connection method	Screw connection
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 12
Screw thread	M3
Tightening torque	0.8 Nm
Stripping length	8 mm

UL specifications

SPD Type	ACC
Nominal voltage	230 V DC
Rated load current I_L	25 A
Power distribution system	1

Type 3 surge protection base element - PLT-SEC-T3-BE - 2905557

Technical data

UL specifications

Nominal frequency	50/60 Hz
-------------------	----------

UL connection data

Conductor cross section AWG	24 ... 12
-----------------------------	-----------

Standards and Regulations


Standards/specifications	IEC 61643-11 2011
	EN 61643-11 2012

Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Diagram




Dimensional drawing



Nominal current depending on ambient temperature

Circuit diagram



Approvals

Approvals

Approvals

KEMA-KEUR / UL Recognized / cUL Recognized / EAC / GL / CSA / cULus Recognized

Type 3 surge protection base element - PLT-SEC-T3-BE - 2905557

Approvals

Ex Approvals

UL Recognized / cUL Recognized / cULus Recognized

Approval details

KEMA-KEUR		http://www.dekra-certification.com	2173868.01
UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 330181
cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 330181
EAC			RU C- DE.A*30.B01561
GL		http://exchange.dnv.com/tari/	14588-15 HH
CSA		http://www.csagroup.org/services-industries/product-listing/	70056020
cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	