



MULTILAYER CERAMIC CHIP CAPACITORS



CGJ Series High Reliability Grade Mid Voltage (100 to 630V)

Type:

**CGJ3 [EIA CC0603]
CGJ4 [EIA CC0805]
CGJ5 [EIA CC1206]
CGJ6 [EIA CC1210]**

**Issue date:
Dec 2014**



REMINDERS

Please read before using this product

SAFETY REMINDERS



REMINDERS

1. If you intend to use a product listed in this catalog for a purpose that may cause loss of life or other damage, you must contact our company's sales window.
2. We may modify products or discontinue production of a product listed in this catalog without prior notification.
3. We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
4. If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
5. Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
6. We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
7. This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.

Notice: Effective January 2013, TDK will use a new catalog number which adds product thickness and packaging specification detail. This new catalog number should be referenced on all catalog orders going forward, and is not applicable for OEM part number orders. Please be aware the last five digits of the catalog number will differ from the item description (internal control number) on the product label. Contact your local TDK Sales representative for more information.

(Example)

Catalog Issued date	Catalog Number	Item Description (On Delivery Label)
Prior to January 2013	C1608C0G1E103J	C1608C0G1E103JT000N
January 2013 and Later	C1608C0G1E103J080AA	C1608C0G1E103JT000N



CGJ Series

Mid Voltage (100 to 630V)

Type: CGJ3 [EIA CC0603], CGJ4 [EIA CC0805], CGJ5 [EIA CC1206], CGJ6 [EIA CC1210]



Features




- Highly reliable products with long lifespans.
- Reliability tests based on MIL-STD requirements.
- Guaranteed TC Bias.
- Sigma Report (enhanced certificate of compliance) is provided for each CGJ lot.
- UHF (Ultra High Frequency) RFID tag to allow integration with customer RFID programs such as inventory management.
- Tamper proof seal to assist in the identification of authentic TDK CGJ products.
- CGJ customer priority backed by TDK factory support.

Applications



- Smart Meter, Smart Grid, LED Lighting
- Industrial Application, Telecom Base Station
- Solar Micro-inverters, Charging station
- Military Communication Equipment
- Class 1 & 2 Medical Equipment
- Applications that require extended life performance

Shape & Dimensions



L	Body Length
W	Body Width
T	Body Height
B	Terminal Width
G	Terminal Spacing



Catalog Number Construction

CGJ • 6 • M • 3 • X7S • 2A • 475 • K • 200 • A • A

Series Name

Dimensions L x W (mm)

Code	Length	Width	Terminal
3	1.60 ± 0.10	0.80 ± 0.10	0.20 min.
4	2.00 ± 0.20	1.25 ± 0.20	0.20 min.
5	3.20 ± 0.20	1.60 ± 0.20	0.20 min.
6	3.20 ± 0.40	2.50 ± 0.30	0.20 min.

Thickness T Code (mm)

Code	Thickness
C	0.60 mm
E	0.80 mm
F	0.85 mm
H	1.15 mm
J	1.25 mm
K	1.30 mm
L	1.60 mm
M	2.00 mm

Voltage Condition for Life Test

Symbol	Condition
1	1 × R.V.
2	2 × R.V.
3	1.5 × R.V.
4	1.2 × R.V.

Temperature Characteristics

Temperature Characteristics	Temperature Coefficient or Capacitance Change	Temperature Range
C0G	0±30 ppm/°C	-55 to +125°C
X7R	±15%	-55 to +125°C
X7S	±22%	-55 to +125°C
X7T	+22/-33%	-55 to +125°C

Rated Voltage (DC)

Code	Voltage (DC)
2A	100V
2D	200V
2H	500V

Nominal Capacitance (pF)

The capacitance is expressed in three digit codes and in units of pico Farads (pF). The first and second digits identify the first and second significant figures of the capacitance. The third digit identifies the multiplier. R designates a decimal point.

Ex. 0R2 = 0.2pF; 103 = 10,000pF; 105 = 1,000,000pF = 100nF = 1μF

Capacitance Tolerance

Code	Tolerance
J	± 5%
K	± 10%

Nominal Thickness

Code	Thickness	Code	Thickness
060	0.60 mm	125	1.25 mm
080	0.80 mm	130	1.30 mm
085	0.85 mm	160	1.60 mm
115	1.15 mm	200	2.00 mm

Packaging Style

Code	Style
A	178 mm Reel, 4 mm Pitch

Special Reserved Code

Code	Description
A	TDK Internal Code



Capacitance Range Chart

CGJ3(1608) [EIA CC0603]

Capacitance Range Chart

Temperature Characteristics: C0G ($0 \pm 30\text{ppm}/^\circ\text{C}$), X7R ($\pm 15\%$), X7S ($\pm 22\%$)

Rated Voltage: 200V (2D), 100V (2A)

Capacitance (pF)	Code	Tolerance	C0G		X7R	X7S
			2D (200V)	2A (100V)	2A (100V)	2A (100V)
100	101	J: $\pm 5\%$ K: $\pm 10\%$				
120	121					
150	151					
180	181					
220	221					
270	271					
330	331					
390	391					
470	471					
560	561					
680	681					
820	821					
1,000	102					
1,200	122					
1,500	152					
2,200	222					
3,300	332					
4,700	472					
6,800	682					
10,000	103					
33,000	333					
47,000	473					
68,000	683					
100,000	104					

Standard Thickness

 0.80 mm



Capacitance Range Chart


CGJ4(2012) [EIA CC0805]

Capacitance Range Chart

Temperature Characteristics: C0G ($0 \pm 30\text{ppm}/^\circ\text{C}$), X7R ($\pm 15\%$), X7S ($\pm 22\%$), X7T ($+ 22\%$, $- 33\%$)
 Rated Voltage: 200V (2D), 100V (2A)

Capacitance (pF)	Code	Tolerance	C0G		X7R		X7S	X7T
			2D (200V)	2A (100V)	2D (200V)	2A (100V)	2A (100V)	2D (200V)
100	101	J: $\pm 5\%$ K: $\pm 10\%$						
120	121							
150	151							
180	181							
220	221							
270	271							
330	331							
390	391							
470	471							
560	561							
680	681							
820	821							
1,000	102							
1,200	122							
1,500	152							
1,800	182							
2,200	222							
2,700	272							
3,300	332							
3,900	392							
4,700	472							
6,800	682							
10,000	103							
15,000	153							
22,000	223							
33,000	333							
47,000	473							
68,000	683							
100,000	104							
330,000	334							
470,000	474							

Standard Thickness





Capacitance Range Chart

CGJ5(3216) [EIA CC1206]

Capacitance Range Chart

Temperature Characteristics: C0G ($0 \pm 30\text{ppm}/^\circ\text{C}$), X7R ($\pm 15\%$), X7S ($\pm 22\%$), X7T ($+ 22\%, - 33\%$)

Rated Voltage: 500V (2H), 200V (2D), 100V (2A),

Capacitance (pF)	Code	Tolerance	C0G			X7R			X7S	X7T	
			2H (500V)	2D (200V)	2A (100V)	2H (500V)	2D (200V)	2A (100V)	2A (100V)	2H (500V)	2D (200V)
100	101	J: $\pm 5\%$ K: $\pm 10\%$									
120	121										
150	151										
180	181										
220	221										
270	271										
330	331										
390	391										
470	471										
560	561										
680	681										
820	821										
1,000	102										
1,200	122										
1,500	152										
1,800	182										
2,200	222										
2,700	272										
3,300	332										
3,900	392										
4,700	472										
5,600	562										
6,800	682										
8,200	822										
10,000	103										
15,000	153										
22,000	223										
33,000	333										
47,000	473										
68,000	683										
100,000	104										
150,000	154										
220,000	224										
330,000	334										
470,000	474										
1,500,000	155										

Standard Thickness

	0.60 mm
	0.85 mm
	1.15 mm
	1.30 mm
	1.60 mm



Capacitance Range Chart

CGJ6(3225) [EIA CC1210]

Capacitance Range Chart

Temperature Characteristics: X7R ($\pm 15\%$), X7S ($\pm 22\%$), X7T (+ 22%, - 33%)
 Rated Voltage: 500V (2H), 200V (2D), 100V (2A)

Capacitance (pF)	Code	Tolerance	X7R			X7S		X7T	
			2H (500V)	2D (200V)	2A (100V)	2A (100V)	2H (500V)	2D (200V)	
47,000	473	K: $\pm 10\%$							
68,000	683								
100,000	104								
150,000	154								
220,000	224								
330,000	334								
470,000	474								
680,000	684								
1,000,000	105								
3,300,000	335								
4,700,000	475								

Standard Thickness
 1.60 mm
 2.00 mm



Capacitance Range Table

Class 1 (Temperature Compensating)

Temperature Characteristics: C0G (-55 to +125°C, 0±30 ppm/°C)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number		
				Rated Voltage Edc: 500V	Rated Voltage Edc: 200V	Rated Voltage Edc: 100V
100 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D101J080AA	CGJ3E2C0G2A101J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A101J060AA
	3216	0.60 ± 0.15	± 5%	CGJ5C4C0G2H101J060AA		
120 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D121J080AA	CGJ3E2C0G2A121J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A121J060AA
	3216	0.60 ± 0.15	± 5%	CGJ5C4C0G2H121J060AA		
150 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D151J080AA	CGJ3E2C0G2A151J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A151J060AA
	3216	0.60 ± 0.15	± 5%	CGJ5C4C0G2H151J060AA		
180 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D181J080AA	CGJ3E2C0G2A181J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A181J060AA
	3216	0.60 ± 0.15	± 5%	CGJ5C4C0G2H181J060AA		
220 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D221J080AA	CGJ3E2C0G2A221J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A221J060AA
	3216	0.60 ± 0.15	± 5%	CGJ5C4C0G2H221J060AA		
270 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D271J080AA	CGJ3E2C0G2A271J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A271J060AA
	3216	0.60 ± 0.15	± 5%	CGJ5C4C0G2H271J060AA		
330 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D331J080AA	CGJ3E2C0G2A331J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A331J060AA
	3216	0.60 ± 0.15	± 5%	CGJ5C4C0G2H331J060AA		
390 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D391J080AA	CGJ3E2C0G2A391J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A391J060AA
	3216	0.60 ± 0.15	± 5%	CGJ5C4C0G2H391J060AA		
470 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D471J080AA	CGJ3E2C0G2A471J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A471J060AA
	3216	0.85 ± 0.15	± 5%	CGJ5F4C0G2H471J085AA		
560 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D561J080AA	CGJ3E2C0G2A561J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A561J060AA
	3216	0.85 ± 0.15	± 5%	CGJ5F4C0G2H561J085AA		
680 pF	1608	0.80 ± 0.10	± 5%		CGJ3E3C0G2D681J080AA	CGJ3E2C0G2A681J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A681J060AA
	3216	0.85 ± 0.15	± 5%	CGJ5F4C0G2H681J085AA		
820 pF	1608	0.80 ± 0.10	± 5%			CGJ3E2C0G2A821J080AA
	2012	0.60 ± 0.15	± 5%		CGJ4C3C0G2D821J060AA	CGJ4C2C0G2A821J060AA
	3216	0.85 ± 0.15	± 5%	CGJ5F4C0G2H821J085AA		
1 nF	1608	0.80 ± 0.10	± 5%			CGJ3E2C0G2A102J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A102J060AA
		0.85 ± 0.15	± 5%		CGJ4F3C0G2D102J085AA	
1.2 nF	3216	0.85 ± 0.15	± 5%	CGJ5F4C0G2H102J085AA		
	1608	0.80 ± 0.10	± 5%			CGJ3E2C0G2A122J080AA
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A122J060AA
1.5 nF		0.85 ± 0.15	± 5%		CGJ4F3C0G2D122J085AA	
	3216	0.85 ± 0.15	± 5%	CGJ5F4C0G2H122J085AA		
	2012	0.60 ± 0.15	± 5%			CGJ4C2C0G2A152J060AA
1.8 nF		0.85 ± 0.15	± 5%		CGJ4F3C0G2D152J085AA	
	3216	1.15 ± 0.15	± 5%	CGJ5H4C0G2H152J115AA		
	2012	0.85 ± 0.15	± 5%			CGJ4F2C0G2A182J085AA
2.2 nF		1.25 ± 0.20	± 5%		CGJ4J3C0G2D182J125AA	
	3216	1.15 ± 0.15	± 5%	CGJ5H4C0G2H182J115AA		
	2012	0.85 ± 0.15	± 5%			CGJ4F2C0G2A222J085AA
2.7 nF		1.25 ± 0.20	± 5%		CGJ4J3C0G2D222J125AA	
	3216	1.15 ± 0.15	± 5%	CGJ5H4C0G2H222J115AA		
	2012	1.25 ± 0.20	± 5%			CGJ4J2C0G2A272J125AA
3.3 nF		1.60 ± 0.20	± 5%		CGJ4J3C0G2D272J125AA	
	3216	1.60 ± 0.20	± 5%	CGJ5L4C0G2H272J160AA		
	2012	1.25 ± 0.20	± 5%			CGJ4J2C0G2A332J125AA
3.3 nF		0.85 ± 0.15	± 5%		CGJ5F3C0G2D332J085AA	
	3216	1.60 ± 0.20	± 5%	CGJ5L4C0G2H332J160AA		



Capacitance Range Table

Class 1 (Temperature Compensating)

Temperature Characteristics: C0G (-55 to +125°C, 0±30 ppm/°C)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number		
				Rated Voltage Edc: 500V	Rated Voltage Edc: 200V	Rated Voltage Edc: 100V
3.9 nF	2012	1.25 ± 0.20	± 5%			CGJ4J2C0G2A392J125AA
		0.60 ± 0.15	± 5%			CGJ5C2C0G2A392J060AA
	3216	0.85 ± 0.15	± 5%	CGJ5F4C0G2H392J085AA		
		1.15 ± 0.15	± 5%		CGJ5H3C0G2D392J115AA	
4.7 nF	2012	1.25 ± 0.20	± 5%			CGJ4J2C0G2A472J125AA
		0.85 ± 0.15	± 5%	CGJ5F4C0G2H472J085AA		CGJ5F2C0G2A472J085AA
	3216	1.15 ± 0.15	± 5%		CGJ5H3C0G2D472J115AA	
		0.85 ± 0.15	± 5%			CGJ5F2C0G2A562J085AA
5.6 nF	3216	1.15 ± 0.15	± 5%	CGJ5H4C0G2H562J115AA	CGJ5H3C0G2D562J115AA	
		1.15 ± 0.15	± 5%	CGJ5H4C0G2H682J115AA		CGJ5H2C0G2A682J115AA
6.8 nF	3216	1.60 ± 0.20	± 5%		CGJ5L3C0G2D682J160AA	
		1.15 ± 0.15	± 5%	CGJ5L4C0G2H822J160AA	CGJ5L3C0G2D822J160AA	CGJ5H2C0G2A822J115AA
8.2 nF	3216	1.15 ± 0.15	± 5%			CGJ5H2C0G2A103J115AA
		1.60 ± 0.20	± 5%	CGJ5L4C0G2H103J160AA		
10 nF	3216	1.15 ± 0.15	± 5%			
		1.60 ± 0.20	± 5%	CGJ5L4C0G2H103J160AA		

Class 2 (Temperature Stable)

Temperature Characteristics: X7R (-55 to +125°C, ±15%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number		
				Rated Voltage Edc: 500V	Rated Voltage Edc: 200V	Rated Voltage Edc: 100V
1 nF	1608	0.80 ± 0.10	± 10%			CGJ3E2X7R2A102K080AA
	3216	1.15 ± 0.15	± 10%	CGJ5H4X7R2H102K115AA		
1.5 nF	1608	0.80 ± 0.10	± 10%			CGJ3E2X7R2A152K080AA
	3216	1.15 ± 0.15	± 10%	CGJ5H4X7R2H152K115AA		
2.2 nF	1608	0.80 ± 0.10	± 10%			CGJ3E2X7R2A222K080AA
	3216	1.15 ± 0.15	± 10%	CGJ5H4X7R2H222K115AA		
3.3 nF	1608	0.80 ± 0.10	± 10%			CGJ3E2X7R2A332K080AA
	3216	1.15 ± 0.15	± 10%	CGJ5H4X7R2H332K115AA		
4.7 nF	1608	0.80 ± 0.10	± 10%			CGJ3E2X7R2A472K080AA
	3216	1.15 ± 0.15	± 10%	CGJ5H4X7R2H472K115AA		
6.8 nF	1608	0.80 ± 0.10	± 10%			CGJ3E2X7R2A682K080AA
	2012	1.25 ± 0.20	± 10%		CGJ4J3X7R2D682K125AA	
10 nF	3216	1.15 ± 0.15	± 10%	CGJ5H4X7R2H682K115AA		
	1608	0.80 ± 0.10	± 10%			CGJ3E2X7R2A103K080AA
15 nF	2012	1.25 ± 0.20	± 10%		CGJ4J3X7R2D103K125AA	
	3216	1.15 ± 0.15	± 10%	CGJ5H4X7R2H103K115AA		
22 nF	2012	1.25 ± 0.20	± 10%		CGJ4J3X7R2D153K125AA	CGJ4J2X7R2A153K125AA
	3216	1.15 ± 0.15	± 10%	CGJ5H3X7R2D153K115AA		
33 nF	2012	1.25 ± 0.20	± 10%		CGJ4J3X7R2D223K125AA	CGJ4J2X7R2A223K125AA
	3216	1.15 ± 0.15	± 10%	CGJ5K4X7R2H153K130AA		
47 nF	2012	1.25 ± 0.20	± 10%		CGJ4J3X7R2D223K115AA	
	3216	1.15 ± 0.15	± 10%	CGJ5K4X7R2H223K130AA		
68 nF	2012	1.25 ± 0.20	± 10%			CGJ4J2X7R2A333K125AA
	3216	1.15 ± 0.15	± 10%	CGJ5L4X7R2H333K160AA	CGJ5L3X7R2D333K160AA	CGJ5H2X7R2A333K115AA
100 nF	2012	1.25 ± 0.20	± 10%			CGJ4J2X7R2A473K125AA
	3216	1.15 ± 0.15	± 10%		CGJ5L3X7R2D473K160AA	CGJ5H2X7R2A473K115AA
150 nF	2012	1.25 ± 0.20	± 10%			
	3216	1.15 ± 0.15	± 10%	CGJ6M4X7R2H473K200AA		
220 nF	2012	1.25 ± 0.20	± 10%		CGJ5L3X7R2D683K160AA	CGJ5L2X7R2A683K160AA
	3216	1.15 ± 0.15	± 10%	CGJ6M4X7R2H683K200AA		
330 nF	2012	1.25 ± 0.20	± 10%		CGJ5L3X7R2D104K160AA	CGJ5L2X7R2A104K160AA
	3216	1.15 ± 0.15	± 10%	CGJ6M3X7R2D104K200AA		
470 nF	2012	1.25 ± 0.20	± 10%			CGJ5L2X7R2A154K160AA
	3216	1.15 ± 0.15	± 10%	CGJ6M3X7R2D154K200AA		
680 nF	2012	1.25 ± 0.20	± 10%			CGJ5H2X7R2A224K115AA
	3216	1.15 ± 0.15	± 10%	CGJ6M3X7R2D224K200AA		
1000 nF	2012	1.25 ± 0.20	± 10%			CGJ5K2X7R2A334K130AA
	3216	1.15 ± 0.15	± 10%	CGJ6M2X7R2A334K200AA		



Capacitance Range Table

Class 2 (Temperature Stable)

Temperature Characteristics: X7R (-55 to +125°C, ±15%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number		
				Rated Voltage Edc: 500V	Rated Voltage Edc: 200V	Rated Voltage Edc: 100V
470 nF	3216	1.60 ± 0.20	± 10%			CGJ5L2X7R2A474K160AA
	3225	2.00 ± 0.20	± 10%			CGJ6M2X7R2A474K200AA
680 nF	3225	1.60 ± 0.20	± 10%	CGJ6L2X7R2A684K160AA		
1 µF	3225	2.00 ± 0.20	± 10%			CGJ6M2X7R2A105K200AA

Class 2 (Temperature Stable)

Temperature Characteristics: X7S (-55 to +125°C, ±22%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number		
				Rated Voltage Edc: 500V	Rated Voltage Edc: 200V	Rated Voltage Edc: 100V
33 nF	1608	0.80 ± 0.10	± 10%			CGJ3E3X7S2A333K080AA
47 nF	1608	0.80 ± 0.10	± 10%			CGJ3E3X7S2A473K080AA
68 nF	1608	0.80 ± 0.10	± 10%			CGJ3E3X7S2A683K080AA
100 nF	1608	0.80 ± 0.10	± 10%			CGJ3E3X7S2A104K080AA
330 nF	2012	1.25 ± 0.20	± 10%			CGJ4J3X7S2A334K125AA
470 nF	2012	1.25 ± 0.20	± 10%			CGJ4J3X7S2A474K125AA
1.5 µF	3216	1.60 ± 0.20	± 10%			CGJ5L3X7S2A155K160AA
3.3 µF	3225	2.00 ± 0.20	± 10%			CGJ6M3X7S2A335K200AA
4.7 µF	3225	2.00 ± 0.20	± 10%			CGJ6M3X7S2A475K200AA

Class 2 (Temperature Stable)

Temperature Characteristics: X7T (-55 to +125°C, +22/-33%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number		
				Rated Voltage Edc: 500V	Rated Voltage Edc: 200V	Rated Voltage Edc: 100V
22 nF	3216	1.15 ± 0.15	± 10%	CGJ5H4X7T2H223K115AA		
33 nF	2012	1.25 ± 0.20	± 10%		CGJ4J3X7T2D333K125AA	
	3216	1.15 ± 0.15	± 10%	CGJ5H4X7T2H333K115AA		
47 nF	2012	1.25 ± 0.20	± 10%		CGJ4J3X7T2D473K125AA	
	3216	1.60 ± 0.20	± 10%	CGJ5L4X7T2H473K160AA		
68 nF	2012	1.25 ± 0.20	± 10%		CGJ4J3X7T2D683K125AA	
100 nF	2012	1.25 ± 0.20	± 10%		CGJ4J3X7T2D104K125AA	
	3225	1.60 ± 0.20	± 10%	CGJ6L4X7T2H104K160AA		
150 nF	3216	1.30 ± 0.20	± 10%		CGJ5K3X7T2D154K130AA	
	3225	2.00 ± 0.20	± 10%	CGJ6M4X7T2H154K200AA		
220 nF	3216	1.60 ± 0.20	± 10%		CGJ5L3X7T2D224K160AA	
330 nF	3225	2.00 ± 0.20	± 10%		CGJ6M3X7T2D334K200AA	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TDK:

<u>CGJ6L4X7T2H104K</u>	<u>CGJ4J3X7S2A334K</u>	<u>CGJ3E3C0G2D121J</u>	<u>CGJ5L2X7R2A154K</u>	<u>CGJ5F4C0G2H471J</u>
<u>CGJ3E2X7R2A472K</u>	<u>CGJ3E3X7S2A104K</u>	<u>CGJ3E2C0G2A391J</u>	<u>CGJ5H3C0G2D472J</u>	<u>CGJ4C2C0G2A181J</u>
<u>CGJ5L3X7T2D224K</u>	<u>CGJ4F2C0G2A182J</u>	<u>CGJ5H2X7R2A333K</u>	<u>CGJ5H4X7R2H222K</u>	<u>CGJ3E3C0G2D471J</u>
<u>CGJ5K4X7R2H223K</u>	<u>CGJ3E3C0G2D271J</u>	<u>CGJ5L3C0G2D822J</u>	<u>CGJ3E2C0G2A221J</u>	<u>CGJ5H2C0G2A682J</u>
<u>CGJ4C2C0G2A122J</u>	<u>CGJ4J2C0G2A392J</u>	<u>CGJ5H4C0G2H152J</u>	<u>CGJ5H4X7R2H102K</u>	<u>CGJ5L3X7R2D473K</u>
<u>CGJ3E2X7R2A152K</u>	<u>CGJ5F3C0G2D332J</u>	<u>CGJ4C2C0G2A101J</u>	<u>CGJ5H4C0G2H682J</u>	<u>CGJ5K2X7R2A334K</u>
<u>CGJ4J2X7R2A153K</u>	<u>CGJ5H2X7R2A224K</u>	<u>CGJ4J3X7R2D103K</u>	<u>CGJ5C4C0G2H151J</u>	<u>CGJ4J2C0G2A332J</u>
<u>CGJ5H4C0G2H562J</u>	<u>CGJ3E2X7R2A332K</u>	<u>CGJ5K4X7R2H153K</u>	<u>CGJ5F2C0G2A562J</u>	<u>CGJ4C2C0G2A121J</u>
<u>CGJ5L4X7R2H333K</u>	<u>CGJ5L3X7R2D333K</u>	<u>CGJ3E3C0G2D391J</u>	<u>CGJ5C4C0G2H331J</u>	<u>CGJ4J3X7R2D682K</u>
<u>CGJ6M3X7S2A335K</u>	<u>CGJ4C2C0G2A561J</u>	<u>CGJ5L3X7S2A155K</u>	<u>CGJ5H4X7R2H682K</u>	<u>CGJ3E2X7R2A103K</u>
<u>CGJ3E2C0G2A121J</u>	<u>CGJ3E3C0G2D331J</u>	<u>CGJ3E2X7R2A102K</u>	<u>CGJ4C2C0G2A331J</u>	<u>CGJ6M2X7R2A105K</u>
<u>CGJ4F3C0G2D122J</u>	<u>CGJ5K3X7T2D154K</u>	<u>CGJ5L3C0G2D682J</u>	<u>CGJ5H3X7R2D223K</u>	<u>CGJ3E3X7S2A683K</u>
<u>CGJ6M4X7R2H683K</u>	<u>CGJ6M3X7R2D104K</u>	<u>CGJ3E2C0G2A681J</u>	<u>CGJ3E3C0G2D221J</u>	<u>CGJ4J2C0G2A272J</u>
<u>CGJ5L4C0G2H332J</u>	<u>CGJ5H2C0G2A822J</u>	<u>CGJ5L3X7R2D104K</u>	<u>CGJ3E2C0G2A561J</u>	<u>CGJ4J3X7T2D683K</u>
<u>CGJ5H4X7T2H333K</u>	<u>CGJ5H3C0G2D392J</u>	<u>CGJ5H4X7R2H472K</u>	<u>CGJ4J3C0G2D272J</u>	<u>CGJ4C2C0G2A471J</u>
<u>CGJ5C4C0G2H271J</u>	<u>CGJ6M4X7R2H473K</u>	<u>CGJ6M2X7R2A474K</u>	<u>CGJ4C2C0G2A152J</u>	<u>CGJ4F3C0G2D102J</u>
<u>CGJ6M2X7R2A334K</u>	<u>CGJ5L4C0G2H272J</u>	<u>CGJ3E3C0G2D681J</u>	<u>CGJ4C3C0G2D821J</u>	<u>CGJ4J2X7R2A223K</u>
<u>CGJ6M3X7S2A475K</u>	<u>CGJ6M4X7T2H154K</u>	<u>CGJ4J2X7R2A473K</u>	<u>CGJ5F2C0G2A472J</u>	<u>CGJ5L2X7R2A474K</u>
<u>CGJ4C2C0G2A271J</u>	<u>CGJ4J3X7T2D473K</u>	<u>CGJ3E3C0G2D151J</u>	<u>CGJ4C2C0G2A221J</u>	<u>CGJ6L2X7R2A684K</u>
<u>CGJ4C2C0G2A681J</u>	<u>CGJ6M3X7R2D154K</u>	<u>CGJ4C2C0G2A391J</u>	<u>CGJ3E2C0G2A122J</u>	<u>CGJ5H4X7T2H223K</u>