Coaxial Cable

pro-**Power**




Description:

Solid PACW, foam PE dielectric, Cu.Foil, PACW braiding 55% coverage, PVC sheath.

Application:

For CATV/MATV, broadband, HDTV and satellite broadcasting transmission use.



Construction:

Conductor:

Material : Solid bare copper 1mm

Dielectric:

Material : Foam PE Nominal Inner Diameter : 4.65mm

Shielding:

Material : Cu. foil 100% coverage
Material : PACW braiding, 55% coverage

Sheath:

Material : PVC
Nominal Outer Diameter : 6.8mm
Colour : Any

Physical Properties:

Minimum Bend Radius : 68mm

Operating Temperature : -15°C to +70°C

Electrical Properties:

Nominal DC Resistance : $25\Omega/km$ Nominal Characteristic Impedance : $75 \pm 3\Omega$ Nominal Capacitance : $55 \pm 2pF/m$

Voltage Test : Core to shielding 2,000V AC/1 minute

Nominal Velocity of Propagation : 81 to 87%

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



Coaxial Cable



Min. Return Loss: (dB/100m)

(MHz)	5 to 30	30 to 470	470 to 862	862 to 2150
(dB)	23	23	20	18

Max. Attenuation (dB/100m)

(MHz)	5	50	100	200	460
(dB)	1.6	4.6	6.5	9.5	15
MHz	860	1,000	1,750	2,150	***
dB	19.5	21.5	29	32.5	***

Part Number Table

Description	Part Number		
Cable, Coaxial, Foam, Black, 50m	CF0094 BLACK 50M		
Cable, Coaxial, Foam, Black, 100m	CF0094 BLACK 100M		
Cable, Coaxial, Foam, White, 100m	CF0094 WHITE 100M		

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

