

Product SKU: C3127.41.86

Product Description: Plenum Cable, Multi-Conductor, Unshielded, NEC Type CMP (UL) c(UL) and/or CL3P, No. of Conductors: 2, Gauge Size (AWG): 16, Conductor/Strands: 19/.0117 BC, Jacket: Natural Flexguard® PVC, Temperature Range: 0°C to +75°C - Natural - 1000 Ft. Reel

Product Category: Electronics - Plenum Cable (available with rip cords - please contact customer service) - Multi-Conductor, Unshielded-PVC Jacket - 16 AWG CONDUCTORS - Natural



Product Construction:

- | | |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conductor: | <ul style="list-style-type: none">• 22 thru 12 AWG fully-annealed, stranded tinned or bare copper per ASTM B3, B8 or B33 |
| Insulation: | <ul style="list-style-type: none">• Color Code: See chart below• Premium grade, color-coded, Flexguard® PVC |
| Jacket: | <ul style="list-style-type: none">• Flexguard® PVC, Natural• Sequential footage markings to facilitate installation• Temperature Range: 0°C to +75°C |

Product Specification:

- | | |
|------------------------------------|---------------------------------------------------------------|
| No. of Conductors: | <ul style="list-style-type: none">• 2 |
| Conductor Size (AWG): | <ul style="list-style-type: none">• 16 |
| Conductor/Strands: | <ul style="list-style-type: none">• 19/.0117 BC |
| Jacket Color: | <ul style="list-style-type: none">• Natural |
| Nominal Insulation Thickness (in): | <ul style="list-style-type: none">• 0.008 |
| Nominal Insulation Thickness (mm): | <ul style="list-style-type: none">• 0.20 |

Nominal Jacket Thickness (in):	<ul style="list-style-type: none">0.015
Nominal Jacket Thickness (mm):	<ul style="list-style-type: none">0.38
Nominal Outside Diameter (in):	<ul style="list-style-type: none">0.147
Nominal Outside Diameter (mm):	<ul style="list-style-type: none">3.73
Nominal C-C Capacitance (pF/ft):	<ul style="list-style-type: none">39.0
Standard Packaging:	<ul style="list-style-type: none">1000' Non-returnable Wood Reels
Standard Package Quantity:	<ul style="list-style-type: none">1
UPC #:	<ul style="list-style-type: none">079407780273
Footnote:	<ul style="list-style-type: none">Nominal Cap. A: Capacitance between conductors
Put-up:	<ul style="list-style-type: none">1000
SCC-14:	<ul style="list-style-type: none">50079407780277
Cube:	<ul style="list-style-type: none">952.63125
Weight Per Unit of Measure:	<ul style="list-style-type: none">.03
ColorOption:	<ul style="list-style-type: none">Natural

Product Information:

Applications:	<ul style="list-style-type: none">Audio systemsBackground musicIntercom systemsPower limited control circuitsSuggested voltage rating: 150 Volts
Compliances:	<ul style="list-style-type: none">Designed to Meet NFPA 262 Flame TestNEC Article 725 (UL: 75Â°C, 150V)NEC Article 800 (UL: 75Â°C, 300V)

Features:

- Easy to terminate
- Flexible

Packaging:

- 1000' (305 m) Reels
- Other put-ups available- consult Customer Service

Reference Charts

[Color Code Chart](#)

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)



**CAROL
BRAND**