

SMD Power Inductor CR43



Halogen Free



Description

- Ferrite drum core construction.
- Magnetically unshielded.
- L × W × H: 4.8 × 4.3 × 3.5 mm Max.
- Product weight: 145mg(Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Halogen Free available.

Environmental Data

- Operating temperature range: -40°C~+100°C (including coil's self temperature rise)
- Storage temperature range: -40°C~+100°C
- Solder reflow temperature: 260 °C peak.


Packaging

- Carrier tape and reel packaging
- 12.9" diameter reel
- 1500pcs per reel



Applications

- Ideally used in A/V equipment, LCD TV, DSC/DVC, Game Machine, DVC, HDD, Notebook PC, etc as DC-DC converter inductors.


Dimension - [mm]



Land pattern and Schematics - [mm]



(1.0~8.2 μ H)



(10~68 μ H)

SMD Power Inductor CR43



Electrical Characteristics

Part Name	Stamp	Inductance (μ H) [within] ※1	D.C.R. (Ω) [Max.] (at 20°C)	Rated Current (A) ※2
CR43NP-1R0MC	1R0	1.0 \pm 20%	48.7m	2.56
CR43NP-1R4MC	1R4	1.4 \pm 20%	56.2m	2.52
CR43NP-1R8MC	1R8	1.8 \pm 20%	63.7m	1.95
CR43NP-2R2MC	2R2	2.2 \pm 20%	71.2m	1.75
CR43NP-2R7MC	2R7	2.7 \pm 20%	78.7m	1.58
CR43NP-3R3MC	3R3	3.3 \pm 20%	86.2m	1.44
CR43NP-3R9MC	3R9	3.9 \pm 20%	93.7m	1.33
CR43NP-4R7MC	4R7	4.7 \pm 20%	108.7m	1.15
CR43NP-5R6MC	5R6	5.6 \pm 20%	125.7m	0.99
CR43NP-6R8MC	6R8	6.8 \pm 20%	131.2m	0.95
CR43NP-8R2MC	8R2	8.2 \pm 20%	146.2m	0.84
CR43NP-100MC	100	10 \pm 20 %	0.182	1.04
CR43NP-120MC	120	12 \pm 20 %	0.210	0.97
CR43NP-150MC	150	15 \pm 20 %	0.235	0.85
CR43NP-180MC	180	18 \pm 20 %	0.338	0.74
CR43NP-220MC	220	22 \pm 20 %	0.378	0.68
CR43NP-270MC	270	27 \pm 20 %	0.522	0.62
CR43NP-330KC	330	33 \pm 10 %	0.540	0.56
CR43NP-390KC	390	39 \pm 10 %	0.587	0.52
CR43NP-470KC	470	47 \pm 10 %	0.844	0.44
CR43NP-560KC	560	56 \pm 10 %	0.937	0.42
CR43NP-680KC	680	68 \pm 10 %	1.117	0.37

※1. Inductance measuring frequency: 1.0 μ H \sim 8.2 μ H ; at 7.96 MHz
10 μ H \sim 68 μ H ; at 2.52 MHz













※2. Rated current: The D.C. current at which the inductance decreases to 90% of it's initial value or when $\Delta t=40^\circ\text{C}$, whichever is lower ($T_a=20^\circ\text{C}$).

SMD Power Inductor CR43



Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT













SMD Power Inductor CR43



Saturation Current & Temperature Rise Graph


— L (20°C) — L (100°C) — ΔT



SMD Power Inductor CR43



Solder Reflow Condition



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)

Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Oberzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com