


CDBA120L-G Thru. CDBA140SL-G

Reverse Voltage: 20 to 40 Volts

Forward Current: 1.0 Amp

RoHS Device




Features

- Ideal for surface mount applications.
- Easy pick and place.
- Plastic package has Underwriters Lab. flammability classification 94V-0.
- Built in strain relief.
- Super low forward voltage drop.

Mechanical data

- Case: JEDEC DO-214AC, molded plastic.
- Terminals: solderable per MIL-STD-750, method 2026.
- Polarity: Color band denotes cathode end.
- Approx. weight: 0.063 grams



Maximum Ratings and Electrical Characteristics

Single phase half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbol	CDBA 120L-G	CDBA 120LL-G	CDBA 140L-G	CDBA 140LL-G	CDBA 140SL-G	Units
Max. repetitive peak reverse voltage	V_{RRM}	20	20	40	40	40	V
Max. DC blocking voltage	V_{DC}	20	20	40	40	40	V
Max. RMS voltage	V_{RMS}	14	14	28	28	28	V
Peak surge forward current, 8.3ms single half sine-wave superimposed on rate load (JEDEC method)	I_{FSM}	35					A
Max. average forward current	I_O	1.0					A
Max. instantaneous forward voltage at 1.0A	V_F	0.38	0.31	0.40	0.34	0.31	V
Max. DC reverse current at $T_A=25^{\circ}C$ rated DC blocking voltage $T_A=80^{\circ}C$	I_R	1.0 40					mA
Max. thermal resistance (Note 1)	$R_{\theta JA}$ $R_{\theta JL}$	88 20					$^{\circ}C/W$
Max. operating junction temperature	T_J	125					$^{\circ}C$
Storage temperature	T_{STG}	-55 to +125					$^{\circ}C$

Notes: 1. Thermal resistance from junction to ambient and junction to lead, P.C.B. mounted on 0.2×0.2 inch copper pad area.

RATING AND CHARACTERISTIC CURVES (CDBA120L-G thru CDBA140SL-G)

Fig.1 Reverse Characteristics




Fig.2 Forward Characteristics




Fig.3 Junction Capacitance




Fig.4 Forward Characteristics




Fig.5 Non-repetitive Forward Surge Current





Fig.6 Current Derating Curve



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com