




STANDARD RECTANGULAR CONNECTORS



✓ Active

 **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE) MTC PQKT1R2SFAC

CN1333-000

TE Internal Number: CN1333-000

[EU RoHS Compliant](#)

[EU ELV Compliant](#)

Product Type **Connector**

Connector Style **Receptacle**

Mating Alignment **Straight**

Mating Alignment Type **Even**

Mating Retention **With**

Product Drawings

[MTC POWER BLOCK QUICK DISCONNECT CONNECTOR KIT](#)

PDF
English

Product Specifications

Product Specification

[MTC Quick-Disconnect Connectors With Removable Contacts](#)

PDF
English



Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Connector

Connector Style

Receptacle

Sealed

No

Shielded

No

Row-to-Row Spacing

2.54 mm [.1 in]

Configuration Features

Number of Positions

20

Number of Rows

2

Electrical Characteristics

Operating Voltage (VAC)

1500

Contact Features

Contact Plating Material

Gold, Nickel

Contact Current Rating (A)

5

	Contact Current Rating (A)	3
Termination Features	Termination Method to Wire/Cable	Crimp
Mechanical Attachment	Mating Alignment	Straight
	Mating Alignment Type	Even
	Mating Retention	With
	Mating Retention Type	JackscREW
	PCB Mount Retention	With
	PCB Mount Retention Type	Crimp
	Contact Retention	Retention Clip
Housing Features	Centerline	2.54 mm [1 in]
Industry Standards	UL Flammability Rating	V0
Statement of Compliance	Statement of Compliance PDF	