

- Screw Terminals
- No Soldering Required
- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
CMB 81..	CMB 8141-0 CMB 8241-0	CMBS 8141-0 CMBS 8241-0	Nickel Plated Brass, PG9 cable gland, accepts 6-8 mm cable diameter, screw terminal accepts up to 18 AWG conductors, 85°C, 250 V, 4 A, Metal, fully shielded Mates with standard key 4-pin cordsets and receptacles	Female Male
CMB 82..	CMB 8151-0 CMB 8251-0	CMBS 8151-0 CMBS 8251-0	Nickel Plated Brass, PG9 cable gland, accepts 6-8 mm cable diameter, screw terminal, accepts up to 18 AWG conductors, 85°C, 60 V, 4 A, metal, fully shielded Mates with standard key 5-pin cordsets and receptacles	Female Male
CMBS 81..				
CMBS 82..	CMB 8181-0	CMBS 8181-0	Nickel Plated Brass, PG9 cable gland accepts 6-8 mm cable diameter, screw terminal accepts up to 18 AWG conductors, 85°C, 60 V, 2 A, metal, fully shielded, mates with standard key 8-pin cordsets and receptacles	Female Male