

RHE5G1H391J1M1A03A

"# " indicates a package specification code.

References



< List of part numbers with package codes > RHE5G1H391J1M1A03A

Shape

L size or outer diameter D (mm)4.0 mm max.W size3.5 mm max.T size2.5 mm max.Lead spacing F5.0 +0.6/-0.2mmLead diameter d0.5 ± 0.05mmW1 size (max.)5.0mm	L F G G (In mm)		
T size 2.5 mm max. Lead spacing F 5.0 +0.6/-0.2mm Lead diameter d 0.5 ± 0.05mm	L size or outer diameter D (mm)	4.0 mm max.	
Lead spacing F 5.0 +0.6/-0.2mm Lead diameter d 0.5 ± 0.05mm	W size	3.5 mm max.	
Lead diameter d 0.5 ± 0.05mm	T size	2.5 mm max.	
	Lead spacing F	5.0 +0.6/-0.2mm	
W1 size (max.) 5.0mm	Lead diameter d	0.5 ± 0.05mm	
	W1 size (max.)	5.0mm	

Packaging Minimum quantity Specifications Ammo pack taping type 2000

Specifications

Capacitance	390pF ±5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X8G(Murata)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 150
Operating temperature range	-55 to 150

1	of	1
---	----	---

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/03/08