

# RHE5G1H681J1M1A03A

"# " indicates a package specification code.

References



< List of part numbers with package codes > RHE5G1H681J1M1A03A

## Shape

L F G G (In mm)		
L size or outer diameter D (mm)	4.0 mm max.	
W size	3.5 mm max.	
T size	2.5 mm max.	
Lead spacing F	5.0 +0.6/-0.2mm	
Lead diameter d	0.5 ± 0.05mm	
W1 size (max.)	5.0mm	

### Packaging Minimum quantity Specifications Ammo pack taping type 2000

# Specifications

Capacitance	680pF ±5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X8G(Murata)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 150
Operating temperature range	-55 to 150

1	of	1

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/03/08