



Ceramic AC Capacitors

Class X1, 440 V_{AC}/Class Y2, 300 V_{AC}




• Dimensions in mm

Impedance (Z) as a function of frequency (f) at T_a = 20 °C (average). Measurement with lead length 50 mm.



I = f (U_R) (typ.)



DESIGN:

Disc capacitors with epoxy coating

RATED VOLTAGE U_R:

(X1): 440 V_{AC}, 50 Hz (IEC 60384-14.2)
 (Y2): 300 V_{AC}, 50 Hz (IEC 60384-14.2)
 250 V_{AC}, 60 Hz (UL1414, CSA C22.2)

DIELECTRIC STRENGTH BETWEEN LEADS:

Component test:

2600 V_{AC}, 50 Hz, 2 s

As repeated test admissible only once with

2340 V_{AC}, 50 Hz, 2 s

Random sampling test (destructive test):

2600 V_{AC}, 50 Hz, 60 s

DIELECTRIC STRENGTH OF BODY INSULATION:

2600 V_{AC}, 50 Hz, 60 s (destructive test)

DISSIPATION FACTOR tan δ:

≤ 25 • 10⁻³

INSULATION RESISTANCE R_{is}:

≥ 6 • 10⁹ Ω

CATEGORY TEMPERATURE RANGE θ_A:

(- 40 to + 125) °C

CLIMATIC CATEGORY ACC. TO EN60068-1:

40/125/21


COATING:

Epoxy, dipped, insulating, flame retarding acc. to UL 94V-0

TAPING AND SPECIAL LEAD CONFIGURATIONS:

On request

MARKING:



WKO 33 pF to 1.0 nF

WKO 1.5 nF to 4.7 nF

All approval marks are also shown on the label.



Ceramic AC Capacitors

Class X1, 440 V_{AC}/Class Y2, 300 V_{AC}

Vishay Draloric

ORDERING INFORMATION, CERAMIC X1 / Y2 CAPACITORS WKO

CAPACITANCE** (pF)	TOL. (%)	D x s (mm)	F ± 1* (mm)	d ± 0.05* (mm)	V ± 0.5* (mm)	ORDERING CODE
CLASS 1 N750						
33	± 10 %, ± 20 %	8.0 x 5.0	7.5	0.6	1.6	WKO330□CP□□□KR
47		8.0 x 5.0				WKO470□CP□□□KR
CLASS 2 K1200						
68	± 10 %, ± 20 %	8.0 x 5.0	7.5	0.6	1.9	WKO680□CP□□□KR
CLASS 2 K1500						
100	± 10 %, ± 20 %	8.0 x 5.0	7.5	0.6	1.9	WKO101□CP□□□KR
CLASS 2 K2000						
150	± 10 %, ± 20 %	8.0 x 5.0	7.5	0.6	1.9	WKO151□CP□□□KR
220		8.0 x 5.0				WKO221□CP□□□KR
330		8.0 x 5.0				WKO331□CP□□□KR
CLASS 2 K4000						
470	± 10 %, ± 20 %	8.0 x 5.0	7.5	0.6	2.0	WKO471□CP□□□KR
680		9.0 x 5.0				WKO681□CP□□□KR
1000		10.0 x 5.0		0.8	1.6	WKO102□CP□□□KR
1500		12.0 x 5.0				WKO152□CP□□□KR
2200		13.0 x 5.0	WKO222□CP□□□KR			
3300		15.0 x 5.0	WKO332□CP□□□KR			
3900		16.0 x 5.0	WKO392□CP□□□KR			
4700		18.0 x 5.0	12.5	WKO472□CP□□□KR		

* Standard lead configuration, other lead spacing and diameter available on request.

** Capacitance values from 1000 pF to 4700 pF: The alternative usage of smaller WKO series is recommended for new application.

ORDERING CODE

□	7th digit	Capacitance Tolerance:	± 10 % = K ± 20 % = M
□□□	10th to 12th digit	Lead Configuration (see General Information)	
R	14th digit	RoHS Compliant Component	

APPROVALS**IEC 60384 - 14 / 2nd Issue (1993) incl. Am. 1 (1995) - Safety Tests****EN 132 400 (1994) - Safety Tests**

That approval together with the CB Test Certificate substitutes the national approval of the following nations:

Belgium	France	Italy	Austria	China	Japan	Spain
Denmark	Greece	Luxembourg	Portugal	Singapore	Poland	United Kingdom
Germany	Ireland	Netherlands	Sweden	Slovenia	Hungaria	Czech Republic
Finland	Iceland	Norway	Switzerland	Korea	Israel	

Y2 - Capacitor: CB-Test Certificate: DE-1-11134-A1 33 pF ... 4.7 nF 300 Vac
 X1 - Capacitor: CB-Test Certificate: DE-1-11134-A1 33 pF ... 4.7 nF 440 Vac
 Minimum thickness of insulation: 0.4 mm



Underwriters Laboratories Inc.

UL 1414	Line-by-pass component.	33 pF ... 4.7 nF	250 Vac	
	Agency Files / Licences	E 183 844 V1 S3		

Canadian Standards Association

CSA C22.2	Line-by-pass component.	33 pF ... 4.7 nF	250 Vac	
No 1-98	Agency Files / Licences	E 183 844 V1 S3		

ORDERING INFORMATION

WKO	392	K	CP	CJ0	K	R
SERIES	CAP. VALUE	TOLERANCE	RATED VOLTAGE	LEAD CONFIGURATION	INTERNAL CODE	RoHS COMPLIANT



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.