

# Wirewound Resistors, Commercial Power, Axial Lead



## FEATURES

- High performance for low cost
- Auto insertable
- CA0001, CA0002 and CA5000 models are supplied with a high temperature silicone coating for additional environmental protection
- Lead forming available
- Compliant to RoHS Directive 2002/95/EC

## APPLICATIONS

Kitchen appliances: Percolators, blenders, mixers, ranges, toasters, deep fryers.  
Entertainment devices: Radios, televisions, computers and power supplies.


Pb-free  
Available

**RoHS\***

COMPLIANT

**GREEN**

(5-2008)\*\*

Available

## STANDARD ELECTRICAL SPECIFICATIONS

| GLOBAL MODEL (1) | HISTORICAL MODEL (1) | POWER RATING<br>$P_{25^{\circ}\text{C}}$ W | RESISTANCE RANGE<br>$\Omega$ | TOLERANCE<br>$\pm \%$ | WEIGHT (typical)<br>g |
|------------------|----------------------|--|------------------------------|-----------------------|-----------------------|
| CA0001           | CA-1                 | 1.0  | 0.1 to 1K                    | 5, 10                 | 0.65                  |
| CA0002           | CA-2                 | 2.0  | 0.1 to 2.4K                  | 5, 10                 | 0.80                  |
| CA4000           | CA-4xxx              | 2.0 to 8.8                                 | 0.1 to 1.02K                 | 5, 10                 | See below             |
| CA5000           | CA-5xxx              | 2.5 to 11.0                                | 0.1 to 7K                    | 5, 10                 | See below             |

### Note

(1) CA4000 and CA5000 model numbers are calculated from the CA4000 power rating of 4 W per inch and CA5000 power rating of 5 W per inch. The last three digits of the model number are the body length of the resistor in inches (decimal is between the first and second digit). Example: CA5150 = 1.50 inches x 5 W per inch = 7.5 W.

## EXAMPLES

| GLOBAL MODEL  | HISTORICAL MODEL | POWER RATING<br>$P_{25^{\circ}\text{C}}$ W | RESISTANCE RANGE<br>$\Omega$ | TOLERANCE<br>$\pm \%$ | WEIGHT (typical)<br>g |
|---------------|------------------|--|------------------------------|-----------------------|-----------------------|
| CA4050/CA5050 | CA-4050/CA-5050  | 2.0/2.5                                    | 0.1 to 170/0.1 to 2.7K       | 5, 10                 | 0.64/0.78             |
| CA4055/CA5055 | CA-4055/CA-5055  | 2.2/2.75                                   | 0.1 to 195/0.1 to 3.1K       | 5, 10                 | 0.65/0.80             |
| CA4060/CA5060 | CA-4060/CA-5060  | 2.4/3.0                                    | 0.1 to 220/0.1 to 3.5K       | 5, 10                 | 0.66/0.82             |
| CA4070/CA5070 | CA-4070/CA-5070  | 2.8/3.5                                    | 0.1 to 270/0.1 to 4.3K       | 5, 10                 | 0.68/0.86             |
| CA4080/CA5080 | CA-4080/CA-5080  | 3.2/4.0                                    | 0.1 to 320/0.1 to 5.1K       | 5, 10                 | 0.70/0.90             |
| CA4090/CA5090 | CA-4090/CA-5090  | 3.6/4.5                                    | 0.1 to 370/0.1 to 5.9K       | 5, 10                 | 0.72/0.94             |
| CA4100/CA5100 | CA-4100/CA-5100  | 4.0/5.0                                    | 0.15 to 420/0.15 to 6.7K     | 5, 10                 | 0.74/0.98             |
| CA4150/CA5150 | CA-4150/CA-5150  | 6.0/7.5                                    | 0.2 to 630/0.2 to 7K         | 5, 10                 | 0.84/1.19             |
| CA4200/CA5200 | CA-4200/CA-5200  | 8.0/10.0                                   | 0.2 to 920/0.2 to 7K         | 5, 10                 | 0.94/1.40             |
| CA4220/CA5220 | CA-4220/CA-5220  | 8.8/11.0                                   | 0.2 to 1.02K/0.2 to 7K       | 5, 10                 | 0.98/1.48             |

## TECHNICAL SPECIFICATIONS

| PARAMETER                       | UNIT                    | CA RESISTOR CHARACTERISTICS                                |
|---------------------------------|-------------------------|--|
| Temperature Coefficient         | ppm/ $^{\circ}\text{C}$ | $\pm 300$ 1 $\Omega$ and above, $\pm 600$ below 1 $\Omega$ |
| Short Time Overload             | -                       | 5 x rated power for 5 s                                    |
| Maximum Working Voltage         | V                       | $(P \times R)^{1/2}$                                       |
| Dielectric Withstanding Voltage | $V_{AC}$                | 600 (CA0001, CA0002 and CA5xxx only)                       |
| Operating Temperature Range     | $^{\circ}\text{C}$      | - 65 to + 275  |
| Terminal Strength (minimum)     | lb                      | 10   |

### Note

- Wirewound CA resistors can reliably function as a fuse and as a resistor. Such components involve compromise between fusing and resistive functions; therefore, each design should be tailored to the application to ensure optimum performance. Contact factory by using the e-mail address at the bottom of this page for design assistance.

## GLOBAL PART NUMBER INFORMATION

Global Part Numbering example: CA000150R00JR05

|   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |  |  |  |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|--|--|--|
| C | A | 0 | 0 | 0 | 1 | 5 | 0 | R | 0 | 0 | J | R | 0 | 5 |  |  |  |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|--|--|--|

| GLOBAL MODEL   | VALUE   | TOLERANCE   | PACKAGING  | SPECIAL  |
|--|---|---|--|--|
| (See Standard Electrical Specifications Global Model column for options) | R = Decimal<br>K = Thousand<br>R1500 = 0.15 $\Omega$<br>1K500 = 1500 $\Omega$ | H = $\pm 3.0 \%$<br>J = $\pm 5.0 \%$<br>K = $\pm 10.0 \%$ | E14 = Lead (Pb)-free bulk<br>E05 = Lead (Pb)-free tape and reel<br>B14 = Tin/lead bulk<br>R05 = Tin/lead tape and reel | (Dash Number) (up to 3 digits) From 1 to 999 as applicable |
| Historical Part Numbering example: CA-1 50 $\Omega$ 5 % R05              |   |   |  |  |
| CA-1   | 50 $\Omega$   | 5 %   | R05  |  |
| HISTORICAL MODEL   | RESISTANCE VALUE  | TOLERANCE CODE  | PACKAGING  |  |

\* Pb containing terminations are not RoHS compliant, exemptions may apply

\*\* Please see document "Vishay Material Category Policy": [www.vishay.com/doc?99902](http://www.vishay.com/doc?99902)


**DIMENSIONS** in inches [millimeters]

Figure 1




Figure 2

**Note**

(1) On some standard reel pack methods, the leads may be trimmed to a shorter length than shown.

| GLOBAL MODEL | DIMENSIONS in inches [millimeters] |               |                   |                              | FIGURE |
|--------------|------------------------------------|---------------|-------------------|------------------------------|--------|
|              | A ± 0.031 [0.794]                  | A' (MAXIMUM)  | B ± 0.001 [0.025] | C                            |        |
| CA0001       | 0.400 [10.16]                      | 0.460 [11.68] | 0.032 [0.813]     | 0.170 maximum [4.32 maximum] | 2      |
| CA0002       | 0.570 [14.48]                      | 0.630 [16.00] | 0.032 [0.813]     | 0.170 maximum [4.32 maximum] | 2      |
| CA4050       | 0.500 [12.70]                      | 0.594 [15.09] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4055       | 0.550 [13.97]                      | 0.644 [16.36] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4060       | 0.600 [15.24]                      | 0.694 [17.63] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4070       | 0.700 [17.78]                      | 0.794 [20.17] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4080       | 0.800 [20.32]                      | 0.894 [22.71] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4090       | 0.900 [22.86]                      | 0.994 [25.25] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4100       | 1.00 [25.40]                       | 1.094 [27.79] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4150       | 1.50 [38.10]                       | 1.594 [40.49] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4200       | 2.00 [50.80]                       | 2.094 [53.19] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4220       | 2.20 [55.88]                       | 2.294 [58.27] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA5050       | 0.500 [12.70]                      | 0.625 [15.88] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5055       | 0.550 [13.97]                      | 0.675 [17.15] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5060       | 0.600 [15.24]                      | 0.725 [18.42] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5070       | 0.700 [17.78]                      | 0.825 [20.96] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5080       | 0.800 [20.32]                      | 0.925 [23.50] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5090       | 0.900 [22.86]                      | 1.025 [26.04] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5100       | 1.00 [25.40]                       | 1.125 [28.58] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5150       | 1.50 [38.10]                       | 1.625 [41.28] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5200       | 2.00 [50.80]                       | 2.125 [53.98] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5220       | 2.20 [55.88]                       | 2.325 [59.06] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |

**MATERIAL SPECIFICATIONS**

**Element:** Copper-nickel alloy or nickel-chrome alloy, depending on resistance value


**Core:** Woven fiberglass

**Coating:** Special high temperature silicone (CA4000 series is not coated)

**Terminals:** Tin/lead electroplated copper (lead (Pb)-free will be 100 % tin)

**End Caps:** Tin plated steel

**Part Marking:** CA0001 and CA0002 are printed with value and tolerance

**DERATING****PERFORMANCE**

| TEST                            | CONDITIONS OF TEST  | TEST LIMITS (EIA RS-344) |
|---------------------------------|---|--------------------------|
| Thermal Shock                   | - 55 °C to + 275 °C, 5 cycles, 30 min dwell time                    | ± (5.0 % + 0.05 Ω) ΔR    |
| Short Time Overload             | 5 x rated power for 5 s   | ± (4.0 % + 0.05 Ω) ΔR    |
| Dielectric Withstanding Voltage | 600 V <sub>AC</sub> for 1 min (CA0001, CA0002 and CA5xxx only)      | ± (2.0 % + 0.05 Ω) ΔR    |
| Low Temperature Storage         | - 65 °C, full rated working voltage for 45 min                      | ± (3.0 % + 0.05 Ω) ΔR    |
| Humidity                        | 75 °C, 90 % to 100 % RH, 240 h                                      | ± (5.0 % + 0.05 Ω) ΔR    |
| Load Life                       | 1000 h at rated power, + 25 °C, 1.5 h "ON", 0.5 h "OFF"             | ± (10.0 % + 0.05 Ω) ΔR   |
| Terminal Strength               | 10 pounds for 30 s; body twisted about axis, 3 x 360° rotations     | ± (2.0 % + 0.05 Ω) ΔR    |
| Resistance to Solder Heat       | Terminal immersed 3.5 s in molten solder at 1/8" to 3/16" from body | ± (4.0 % + 0.05 Ω) ΔR    |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.