



| Parameter              | Rating | Units                |
|------------------------|--------|----------------------|
| Blocking Voltage       | 350    | $V_P$                |
| Load Current           | 120    | $mA_{rms} / mA_{DC}$ |
| On-Resistance (max)    | 30     | $\Omega$             |
| LED Current to operate | 2      | mA                   |

### Features

- 1500V<sub>rms</sub> Input/Output Isolation
- Arc-Free With No Snubbing Circuits
- No EMI/RFI Generation
- Immune to Radiated EM Fields
- Wave Solderable
- Tape & Reel Version Available
- Small 8-Pin SOIC Package

### Applications

- Telecommunications
- Security
  - Passive Infrared Detectors (PIR)
  - Data Signaling
  - Sensor Circuitry
- Instrumentation
  - Multiplexers
  - Data Acquisition
  - Electronic Switching
  - I/O Subsystems
- Medical Equipment—Patient/Equipment Isolation
- Aerospace
- Industrial Controls

### Description

The CPC2030N is a miniature device with two independent normally-open (1-Form-A) solid state relays in an 8-pin SOIC package that employs optically coupled MOSFET technology to provide 1500V<sub>rms</sub> of input to output isolation.

Optically coupled outputs using the patented OptoMOS architecture are controlled by a highly efficient infrared LED.

The CPC2030N uses IXYS Integrated Circuits Division's state of the art, double-molded vertical construction packaging to produce one of the world's smallest relays. The CPC2030N offers substantial board space savings over the competitor's larger 8-pin SOIC relay.


### Approvals

- UL Recognized Component: File E76270
- CSA Approval Pending
- EN/IEC 60950-1 Certified Component:  
TUV Certificate B 13 12 82667 003


### Ordering Information

| Part #     | Description            |
|------------|------------------------|
| CPC2030N   | 8-Pin SOIC (50/tube)   |
| CPC2030NTR | 8-Pin SOIC (2000/reel) |

### Pin Configuration



### Switching Characteristics of Normally-Open (Form A) Devices



## Absolute Maximum Ratings @ 25°C

| Parameter                            | Ratings     | Units            |
|--------------------------------------|-------------|------------------|
| Blocking Voltage                     | 350         | V <sub>P</sub>   |
| Reverse Input Voltage                | 5           | V                |
| Input Control Current                | 50          | mA               |
| Peak (10ms)                          | 1           | A                |
| Input Power Dissipation              | 70          | mW               |
| Total Power Dissipation <sup>1</sup> | 600         | mW               |
| Isolation Voltage, Input to Output   | 1500        | V <sub>rms</sub> |
| Operational Temperature              | -40 to +85  | °C               |
| Storage Temperature                  | -40 to +125 | °C               |

<sup>1</sup> Derate linearly 5mW / °C

*Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at conditions beyond those indicated in the operational sections of this data sheet is not implied.*

*Typical values are characteristic of the device at +25°C, and are the result of engineering evaluations. They are provided for information purposes only, and are not part of the manufacturing testing requirements.*

## Electrical Characteristics @ 25°C













| Parameter                                      | Conditions                                       | Symbol            | Min | Typ  | Max  | Units                                |
|------------------------------------------------|--------------------------------------------------|-------------------|-----|------|------|--------------------------------------|
| <b>Output Characteristics</b>                  |                                                  |                   |     |      |      |                                      |
| Load Current                                   |                                                  |                   |     |      |      |                                      |
| Continuous <sup>1</sup>                        | I <sub>F</sub> =2mA                              | I <sub>L</sub>    | -   | -    | 120  | mA <sub>rms</sub> / mA <sub>DC</sub> |
| Peak                                           | t=10ms                                           | I <sub>LPK</sub>  | -   | -    | ±350 | mA <sub>P</sub>                      |
| On-Resistance <sup>2</sup>                     | I <sub>L</sub> =120mA                            | R <sub>ON</sub>   | -   | 19.5 | 30   | Ω                                    |
| Off-State Leakage Current                      | V <sub>L</sub> =350V <sub>P</sub>                | I <sub>LEAK</sub> | -   | -    | 1    | μA                                   |
| Switching Speeds                               |                                                  |                   |     |      |      |                                      |
| Turn-On                                        | I <sub>F</sub> =5mA, V <sub>L</sub> =10V         | t <sub>on</sub>   | -   | 0.76 | 2    | ms                                   |
| Turn-Off                                       |                                                  | t <sub>off</sub>  | -   | 0.36 | 1    |                                      |
| Output Capacitance                             | I <sub>F</sub> =0mA, V <sub>L</sub> =50V, f=1MHz | C <sub>OUT</sub>  | -   | 9    | -    | pF                                   |
| Capacitance, Input to Output                   | V <sub>IO</sub> =0V, f=1MHz                      | C <sub>IO</sub>   | -   | 1    | -    | pF                                   |
| <b>Input Characteristics</b>                   |                                                  |                   |     |      |      |                                      |
| Input Control Current to Activate <sup>3</sup> | I <sub>L</sub> =120mA                            | I <sub>F</sub>    | -   | -    | 2    | mA                                   |
| Input Control Current to Deactivate            | -                                                | I <sub>F</sub>    | 0.1 | -    | -    | mA                                   |
| Input Voltage Drop                             | I <sub>F</sub> =5mA                              | V <sub>F</sub>    | 0.9 | 1.2  | 1.4  | V                                    |
| Reverse Input Current                          | V <sub>R</sub> =5V                               | I <sub>R</sub>    | -   | -    | 10   | μA                                   |

<sup>1</sup> Load current derates linearly from 120mA @ 25°C to 60mA @ 85°C, and must be derated for both poles operating simultaneously.

<sup>2</sup> Measurement taken within 1 second of on-time.


<sup>3</sup> For applications requiring high temperature operation (greater than 60°C) a minimum LED drive current of 4mA is recommended.

# PERFORMANCE DATA @ 25°C (Unless Otherwise Noted)\*



\*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

# PERFORMANCE DATA @ 25°C (Unless Otherwise Noted)\*



\*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

## Manufacturing Information

### Moisture Sensitivity



All plastic encapsulated semiconductor packages are susceptible to moisture ingress. IXYS Integrated Circuits Division classified all of its plastic encapsulated devices for moisture sensitivity according to the latest version of the joint industry standard, **IPC/JEDEC J-STD-020**, in force at the time of product evaluation. We test all of our products to the maximum conditions set forth in the standard, and guarantee proper operation of our devices when handled according to the limitations and information in that standard as well as to any limitations set forth in the information or standards referenced below.

Failure to adhere to the warnings or limitations as established by the listed specifications could result in reduced product performance, reduction of operable life, and/or reduction of overall reliability.

This product carries a **Moisture Sensitivity Level (MSL) rating** as shown below, and should be handled according to the requirements of the latest version of the joint industry standard **IPC/JEDEC J-STD-033**.

| Device   | Moisture Sensitivity Level (MSL) Rating |
|----------|-----------------------------------------|
| CPC2030N | MSL 3                                   |

### ESD Sensitivity



This product is **ESD Sensitive**, and should be handled according to the industry standard **JESD-625**.

### Soldering Profile

This product has a maximum body temperature and time rating as shown below. All other guidelines of **J-STD-020** must be observed.

| Device   | Maximum Temperature x Time | Maximum Reflow Cycles |
|----------|----------------------------|-----------------------|
| CPC2030N | 260°C for 30 seconds       | 3                     |


### Board Wash

IXYS Integrated Circuits Division recommends the use of no-clean flux formulations. However, board washing to remove flux residue is acceptable. Since IXYS Integrated Circuits Division employs the use of silicone coating as an optical waveguide in many of its optically isolated products, the use of a short drying bake could be necessary if a wash is used after soldering processes. Chlorine- or Fluorine-based solvents or fluxes should not be used. Cleaning methods that employ ultrasonic energy should not be used.




## MECHANICAL DIMENSIONS

### CPC2030N



### CPC2030NTR Tape & Reel



#### NOTES:

1. All dimensions in millimeters
2. 10 sprocket hole pitch cumulative tolerance ± 0.20.
3. Carrier camber is within 1mm in 250mm.
4. Tape material : Black Conductive Polystyrene Alloy.
5. All dimensions meet EIA-481-C requirements.
6. Thickness : 0.30 ± 0.05mm.

For additional information please visit our website at: [www.ixysic.com](http://www.ixysic.com)

IXYS Integrated Circuits Division makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in IXYS Integrated Circuits Division's Standard Terms and Conditions of Sale, IXYS Integrated Circuits Division assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of IXYS Integrated Circuits Division's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. IXYS Integrated Circuits Division reserves the right to discontinue or make changes to its products at any time without notice.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[IXYS:](#)

[CPC2030N](#) [CPC2030NTR](#)