Open-Access [™] Cable Management System



specifications

Cable management solutions shall be capable of managing cable on the front and rear of any standard EIA 19" rack or cabinet. Panels shall be constructed of a steel panel with plastic D-rings attached. Horizontal D-rings shall snap into panels and vertical D-rings shall be screw mounted to rack. Horizontal panels shall have pass-through holes and shall be available in both front and rear versions and front only versions.



technical information

D-ring mounting options:	Horizontal D-rings snap into Open-Access [™] panels only; vertical D-rings screw into EIA racks	
Panel mounting options:	Mount to any EIA 19" rack or cabinet	
Packaging:	Cable management panels include horizontal D-rings pre-installed onto panels and #12-24 and M6 mounting hardware	

key features and benefits

Modular, snap-in D-rings	Provides flexibility for system requirements	
Flexible D-rings	Allows easy access to cables for moves, adds, and changes	
Rounded D-rings	Prevents cable snags	
Cable pass-through holes on panels	Provides ease of installation and cable maintenance	
Available in a variety of styles	Suitable for large and small cabling installations	
Lightweight, sturdy construction	Easy to work with while still providing durability	
Optional snap-on cover	Provides an aesthetically pleasing solution	

Open-Access[™] Cable Management System

2 Rack Space Panel, Front and Rear

19" 3 x 3 D-rings on front and 3 x 5 D-rings on rear: CMPH2

2 Rack Space Panel, Front Only		
19" 3 x 3 D-rings: 19" 3 x 3 D-rings:		
2 Rack Space Pane	l, Front and Rear	
19" 1.5 x 3 D-rings on front and 1.5 x 5 on rear:	CMPH1	
1 Rack Space Pane	l, Front Only	
19" 1.5 x 3 D-rings: 19" 1.5 x 5 D-rings:		
2 Rack Space Horiz	ontal D-Rings	
3 x 3:	CMDRH2	
1 Rack Space Horiz	contal D-Rings	
1.5 x 3:	CMDRH1	
Vertical D-Rings		
2 RU: 1 RU: Center:	CMVDR2 CMVDR1 CMVDRC	
Covers		
19" 2 RU: 19" 1 RU:	CMPH2C CMPH1C	

applications

Panduit[®] Open-Access[™] Cable Management components offer an economical cable management solution for current and future applications. D-rings provide an "open" and efficient way to manage cable on any standard EIA 19" rack or cabinet. The panels can be used in multimedia applications with all coax, copper and fiber optic cables The Open-Access[™] System offers increased flexibility due to the modularity of the D-rings. Components can be easily added as system requirements grow, providing the lowest installed cost. The Open-Access[™] Cable Management System can be used with Mini-Com[®] Modular Patch Panels, Opticom[®] Enclosures and NetRunner[™] Vertical Cable Management and Racks for a total system solution now and in the future.

Open-Access[™] Cable Management System



CMPH1 H = 1.72" (42.67mm) D = 8.57" (217.6mm) W = 19.0" (482.6mm)



CMPHF1 H = 1.72" (42.67mm) D = 3.42" (86.87mm) W = 19.0" (482.6mm)



CMPH2 H = 3.47" (88.1mm) D = 8.58" (217.8mm) W = 19.0" (482.6mm)



CMPHF2 H = 3.47" (88.1mm) D = 3.42" (86.87mm) W = 19.0" (482.6mm)



CMPHHF1 H = 1.72" (42.67mm) D = 5.38" (136.65mm) W = 19.0" (482.6mm)



CMDRHD2 H = 3.23" (82.0mm) D = 5.38" (136.5mm) W = 1.50" (38.1mm)



CMPHH2 H = 3.47" (88.1mm) D = 5.38" (136.65mm) W = 19.0" (482.6mm)



CMVDR2 H = 3.30" (83.82mm) D = 5.72" (145.16mm) W = 2.38" (60.32mm)

PANDUIT CANADA Markham, Ontario cs-cdn@panduit.com Phone: 800.777.3300 PANDUIT EUROPE LTD. London, UK cs-emea@panduit.com Phone: 44.20.8601.7200 PANDUIT SINGAPORE PTE. LTD. Republic of Singapore cs-ap@panduit.com Phone: 65.6305.7575 PANDUIT JAPAN Tokyo, Japan cs-japan@panduit.com Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA Guadalajara, Mexico cs-la@panduit.com Phone: 52.33.3777.6000 PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia cs-aus@panduit.com Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

For more information



Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com or by phone: 800.777.3300 ©2014 Panduit Corp. ALL RIGHTS RESERVED. **RKSP140--WW-ENG** Replaces WW-RKSP18 4/2014