+ + J DATE 3-24-06 THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NER ВЧ E S [3,4E] 50 MICRO INCH GOLD PLATING AT MATING JACK SIDE WITH CONTINUOUS NICKEL UNDERPLATING. RELEASED [E, B, 1] . 72 TERMINATION CAP SEE DESCRIPTION TO JACK HOUSING PRODUCT I ON NOTE 2 SELECTIVE TIN-LEAD POST-PLATING ON IDC TERMINATIONS WITH CONTINUOUS NICKEL UNDERPLATING. (JACK HOUSING) PANDUIT NO. CJ88XXXY TON SI 02479-335 E S N ō BE USED IN 닺 8 POSITION, 8 WIRE TERMINATION CAP IS COLOR CODED FOR EIA/TIA 568A AND/OR 568B WIRING. CUST DESCRIPTION SUP ANY WAY DETRIMENTAL 1. SEE CURRENT CATALOG FOR ADDITIONAL PART
NUMBER SUFFIXES TO INDICATE COLOR AND OR
PACKAGE QUANTITY.

2. MATERIAL:
JACK HOUSING - ABS NOMINAL WALL THICKNESS .078(2:0).
TERMINATION CAP - POLYCARBONATE
ALL MINI - JACK 8 POSITION, 8 WIRE CONNECTOR
MODULES ARE UNIVERSAL IN DESIGN.
THEY WILL ACCEPT TWO, THREE, OR FOUR PAIR
MODULAR PLUGS WITHOUT DAMAGE. ហ <u>ი</u> 4. NOTE: DRAWN BY ZEZ снескер ву CAD FILENAME/LAYERS 03-24-06 UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: DIMENSIONS IN PARENTHESIS ARE IN METRIC. (.xx) ± .03 (.xxx) ± .005 THIS PART IS DESIGNED FOR USE WITH MINI-COM PLATES & BOXES.
MEETS ALL CATEGORY 3 PERFORMANCE REQUIREMENTS AS DEFINED BY EIA/TIA. MINI-JACK CATEGORY 3 TWISTED PAIR CONNECTOR MODULE CUSTOMER DRAWING MAT'L: ō M02479MV\_DC335\_00A.PRT S THE INTERESTS NOTED CORP. 유 1.62 02479-335 ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION. UNLESS OTHERWISE SPECIFIED, PANDUIT CORP. TINLEY PARK, ILLINOIS WE I GHT LB/100 P NONE D PCS  $\rightarrow$ 

+