

4805 (3/11)

/3-146426-1 30 78.33 [3.084] 76.20 [3.000] 62 3-146426-0 75.79 [2.984] 29 60 73.66 [2.900] 71.12 [2.800] 28 58 2-146426-9 73.25 [2.884] 68,58 [2.700] 2-146426-8 70.71 [2.784] 27 56 26 2-146426-7 68.17 [2.684] 66.04 [2.600] 54, 25 2-146426-6 65.63 [2.584] 63.50 [2.500] 63.09 [2.484] 24 2-146426-5 60.96 [2.400] 50 60.55 [2.384] 58.42 [2.300] 23 48 2-146426-4 2-146426-3 58.01 [2.284] 55.88 [2.200] 22 21/ 2-146426-2 55.47 [2.184] 53.34 [2.100] 44 2-146426-1 52.93 [2.084] 50.80 [2.000] 42 50.39 [1.984] 48.26 [1.900] (19 40 2-146426-0 45.72 [1.800] 38 1-146426-9 47.85 [1.884] 1-146426-8 1 36 45.31 [1.784] 43.18 [1.700]/ 16 1 - 146426 - 742.77 [1.684] 34 40.64 [1.696] 1-146426-6 40.23 [1.584] 38.10 [1.500] 15 32 35.56 [1.400] 30 1-146426-5 37.69 [1.484] 14 1-146426-4 33.02/[1.300] 35.15 [1.384] 13 28 1-146426-3 32.61 [1.284] 12 26 30.48 [1.200] 2/.94 [1.100] 1-146426-2 30.07 [1.184] 1 1 24 /25.40 [1.000] 10 1 - 146426 - 127.53 [1.084] 22 1-146426-0 20 22.86 [.900] 24.99 [.984] 146426-9 18 22.45 [.884] 20.32 [.800] 146426-8 16 19.91 [.78*4*/] 17.78 [.700] 146426-7 17.37 [.6,84] 15.24 [.600] 14 146426-6 14.83 [.584] 12.70 [.500] 12 146426-5 12.29/[.484] 10.16 [.400] 10 146426-4 9.75 [.384] 8.99 [.300] 146426-3 7/.21 [.284] 6.45 [.200] 146426-2 4.67 [.184] 2.54 [.100] 146426-1 2.33 [.092] NO OF NUMBER В POSN THIS DRAWING IS A CONTROLLED DOCUMENT. **ETE** TE Connectivity TOLERANCES UNLESS OTHERWISE SPECIFIED: mm [INCHES] HEADER ASSY, MOD II, BREAKAWAY, DBL ROW, .100 X.100 CL, VERT, .025 SQ ± -± 0.13[.005] ± -± -POSTS, WITH RETENTION FEATURE APPLICATION SPEC SIZE CAGE CODE DRAWING NO 1 00779 **C-**146426 HOUSING: FLAME RETARDANT THERMOPLASTIC COLOR: BLACK POST: COPPER ALLOY SCALE 4:1 SHEET 1 OF REV G USTOMER DRAWING

1	TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
2	THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOU
3	RETENTION FEATURE ON SOLDERTAILS LOCATED AT MANUFACTURER'S OPTION.

101.19 [3.984]

98.65 [3.884]

96.11 [3.784]

93.57 [3.684]

91.03 [3.584]

88.49 [3.484]

85.95 [3,384]

83.41 [3.284]

80.87 [3.184]

THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
RETENTION FEATURE ON SOLDERTAILS LOCATED AT MANUFACTURER'S OPTION.
THIS DIMENSION WILL BE 4.67±0.41 [.184±.016] FOR THE 2 POSITION CONFIGURATION
OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

99.06 [3.900]

96.52 [3.800]

93.98 [3.700]

91.44 [3.600]

88.90 [3.500]

86.36 [3.400]

83.82 [3.300]

81.28 [3.200]

78.74 [3.100]

39

38

37

36

35

34

33

32

31

80

78

76

74

72

70

68

66

64

AD

REVISIONS

DESCRIPTION

G REVISED PER ECO-14-000260

DATE DWN APVE

07JUL2014 NK MM

4-146426-0

3-146426-9

3-146426-8

3-146426-7

3−146426*-*∕6

3-146426-5

3-146426-4

3-1/46426-3

3/146426-2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: