

**LOCTITE 4105** 

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 14

SDS No.: 173363

V002.6 Revision: 03.02.2015

printing date: 07.04.2015

Replaces version from: 21.11.2013

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

LOCTITE 4105

#### **Contains:**

Ethyl 2-cyanoacrylate

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel Limited

2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 Fax-no.: +44 1606 863762

ua-productsafety.uk@uk.henkel.com

### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation. Target organ: respiratory tract irritation

### **Classification (DPD):**

Xi - Irritant

R36/37/38 Irritating to eyes, respiratory system and skin.

#### 2.2. Label elements

#### Label elements (CLP):

MSDS-No.: 173363 LOCTITE 4105 Page 2 of 14

V002.6

Hazard pictogram:



Signal word: Warning

**Hazard statement:** H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

**Supplemental information** EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of

children.

Contains Hydroquinone; Phthalic anhydride. May produce an allergic reaction.

**Precautionary statement:** P261 Avoid breathing vapours.

**Prevention** P280 Wear protective gloves/eye protection.

**Precautionary statement:** P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

**Response** contact lenses, if present and easy to remove. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

**Precautionary statement:** P501 Dispose of waste and residues in accordance with local authority requirements.

Disposal

### Label elements (DPD):

Xi - Irritant



Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

Safety phrases:

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Additional labeling:

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Contains Phthalic anhydride, Hydroquinone. May produce an allergic reaction.

# 2.3. Other hazards

None if used properly.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### General chemical description:

Cyanoacrylate Adhesive

MSDS-No.: 173363 LOCTITE 4105 Page 3 of 14

V002.6

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethyl 2-cyanoacrylate 7085-85-0	230-391-5 01-2119527766-29	50- 100 %	Serious eye irritation 2 H319  Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315
Hydroquinone 123-31-9	204-617-8 01-2119524016-51	0,1-< 1 %	Carcinogenicity 2 H351 Germ cell mutagenicity 2 H341 Acute toxicity 4; Oral H302 Serious eye damage 1 H318 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 1 H400 M factor: 10 M factor (Chron Aquat Tox): 10
Phthalic anhydride 85-44-9	201-607-5 01-2119457017-41	0,1-< 1 %	Acute toxicity 4; Oral H302  Specific target organ toxicity - single exposure 3 H335  Skin irritation 2 H315  Serious eye damage 1 H318  Respiratory sensitizer 1 H334  Skin sensitizer 1 H317

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethyl 2-cyanoacrylate 7085-85-0	230-391-5 01-2119527766-29	50 - 100 %	Xi - Irritant; R36/37/38
Hydroquinone 123-31-9	204-617-8 01-2119524016-51	0,1 -< 1 %	carcinogenic, category 3; R40 Mutagen category 3; R68 Xn - Harmful; R22 Xi - Irritant; R41 R43 N - Dangerous for the environment; R50
Phthalic anhydride 85-44-9	201-607-5 01-2119457017-41	0,1 - < 1 %	Xn - Harmful; R22 Xi - Irritant; R37/38, R41 R42/43

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

MSDS-No.: 173363 LOCTITE 4105 Page 4 of 14

V002.6

#### Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

#### Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

#### Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

#### 4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Fine water spray

#### Extinguishing media which must not be used for safety reasons:

None known

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

#### **Additional information:**

In case of fire, keep containers cool with water spray.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid skin and eye contact.

#### 6.2. Environmental precautions

Do not let product enter drains.

#### 6.3. Methods and material for containment and cleaning up

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

#### 6.4. Reference to other sections

See advice in section 8

MSDS-No.: 173363 LOCTITE 4105 Page 5 of 14

V002.6

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Ventilation (low level) is recommended when using large volumes

Use of dispensing equipment is recommended to minimise the risk of skin or eye contact

# Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

### 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)

### 7.3. Specific end use(s)

Adhesive

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient	ppm	mg/m <sup>3</sup>	Type	Category	Remarks
ETHYL CYANOACRYLATE 7085-85-0	0,3	1,5	Short Term Exposure Limit (STEL):		EH40 WEL
CARBON BLACK		7	Short Term Exposure		EH40 WEL
1333-86-4		/	Limit (STEL):		EH40 WEL
CARBON BLACK		3,5	Time Weighted Average		EH40 WEL
1333-86-4			(TWA):		
HYDROQUINONE		0,5	Time Weighted Average		EH40 WEL
123-31-9			(TWA):		
PHTHALIC ANHYDRIDE		12	Short Term Exposure		EH40 WEL
85-44-9			Limit (STEL):		
PHTHALIC ANHYDRIDE		4	Time Weighted Average		EH40 WEL
85-44-9			(TWA):		

MSDS-No.: 173363 LOCTITE 4105 Page 6 of 14

V002.6

# $\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value		Remarks		
			mg/l	ppm	mg/kg	others	
Hydroquinone	aqua					0,114 μg/L	
123-31-9	(freshwater)						
Hydroquinone	aqua (marine					0,0114 µg/L	
123-31-9	water)						
Hydroquinone	sediment					0,98 µg/kg	
123-31-9	(freshwater)						
Hydroquinone	sediment					0,097 µg/kg	
123-31-9	(marine water)						
Hydroquinone	aqua					0,00134 mg/L	
123-31-9	(intermittent						
	releases)						
Hydroquinone	soil					0,129 µg/kg	
123-31-9							
Hydroquinone	STP					0,71 mg/L	
123-31-9							
Phthalic anhydride	soil				0,173		
85-44-9					mg/kg		
Phthalic anhydride	STP					10 mg/L	
85-44-9							
Phthalic anhydride	sediment				3,8 mg/kg		
85-44-9	(freshwater)						
Phthalic anhydride	sediment				0,38 mg/kg		
85-44-9	(marine water)						
Phthalic anhydride	aqua (marine					0,1 mg/L	
85-44-9	water)						
Phthalic anhydride	aqua					5,6 mg/L	
85-44-9	(intermittent			1			
	releases)						
Phthalic anhydride	aqua					1 mg/L	
85-44-9	(freshwater)						

MSDS-No.: 173363 LOCTITE 4105 Page 7 of 14

V002.6

# **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethyl 2-cyanoacrylate 7085-85-0	Workers	Inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	Workers	Inhalation	Long term exposure - systemic effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	Inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	Inhalation	Long term exposure - systemic effects		9,25 mg/m3	
Hydroquinone 123-31-9	Workers	Dermal	Long term exposure - systemic effects		128 mg/kg bw/day	
Hydroquinone 123-31-9	Workers	Inhalation	Long term exposure - systemic effects		7 mg/m3	
Hydroquinone 123-31-9	Workers	Inhalation	Long term exposure - local effects		1 mg/m3	
Hydroquinone 123-31-9	general population	Dermal	Long term exposure - systemic effects		64 mg/kg bw/day	
Hydroquinone 123-31-9	general population	Inhalation	Long term exposure - systemic effects		1,74 mg/m3	
Hydroquinone 123-31-9	general population	Inhalation	Long term exposure - local effects		0,5 mg/m3	
Phthalic anhydride 85-44-9	Workers	inhalation	Long term exposure - systemic effects		32,2 mg/m3	
Phthalic anhydride 85-44-9	Workers	Dermal	Long term exposure - systemic effects		10 mg/kg bw/day	
Phthalic anhydride 85-44-9	general population	inhalation	Long term exposure - systemic effects		8,6 mg/m3	
Phthalic anhydride 85-44-9	general population	Dermal	Long term exposure - systemic effects		5 mg/kg bw/day	
Phthalic anhydride 85-44-9	general population	oral	Long term exposure - systemic effects		5 mg/kg bw/day	

# **Biological Exposure Indices:**

None

# 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

MSDS-No.: 173363 LOCTITE 4105 Page 8 of 14

V002.6

#### Hand protection:

The use of chemical resistant gloves such as Nitrile is recommended.

Polyethylene or polypropylene gloves are recommended when using large volumes.

Do not use PVC, rubber or nylon gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Wear protective glasses.

#### Skin protection:

Wear suitable protective clothing.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance liquid

liquid black

Odor Irritating

Odour threshold No data available / Not applicable

pH No data available / Not applicable

Initial boiling point > 149 °C (> 300.2 °F)

Flash point 80 - 93 °C (176 - 199.4 °F); Tagliabue closed cup

Decomposition temperature No data available / Not applicable

Vapour pressure < 0,6 mbar

(25 °C (77 °F))

Vapour pressure < 700 mbar

(50 °C (122 °F))

Density 1,1 g/cm<sup>3</sup>

(20 °C (68 °F))

Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable
Solubility (qualitative)
Polymerises in presence of water.

(Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable No data available / Not applicable Flammability No data available / Not applicable Auto-ignition temperature **Explosive limits** No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable No data available / Not applicable Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable Oxidising properties

### 9.2. Other information

No data available / Not applicable

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

# 10.3. Possibility of hazardous reactions

See section reactivity

MSDS-No.: 173363 LOCTITE 4105 Page 9 of 14

V002.6

#### 10.4. Conditions to avoid

No decomposition if used according to specifications.

#### 10.5. Incompatible materials

See section reactivity

#### 10.6. Hazardous decomposition products

carbon oxides.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

### STOT-single exposure:

May cause respiratory irritation.

#### Oral toxicity:

Cyanoacrylates are considered to have relatively low toxicity. Acute oral LD50 is >5000mg/kg (rat). It is almost impossible to swallow as it rapidly polymerises in the mouth.

#### Inhalative toxicity:

Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals In dry atmosphere with < 50% humidity, vapours may irritate the eyes and respiratory system

#### Skin irritation:

Causes skin irritation.

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg Due to polymerisation at the skin surface allergic reaction is unlikely to occur

#### Eye irritation:

Causes serious eye irritation.

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

#### Sensitizing:

May cause allergic reaction.

### Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Ethyl 2-cyanoacrylate	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute
7085-85-0						Oral Toxicity)
Hydroquinone	LD50	367 mg/kg	oral		rat	OECD Guideline 401 (Acute
123-31-9						Oral Toxicity)
Phthalic anhydride	LD50	1.530 mg/kg	oral		rat	
85-44-9						

### Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50	> 2.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Phthalic anhydride 85-44-9	LD50	> 10.000 mg/kg	dermal		rabbit	

MSDS-No.: 173363 LOCTITE 4105 Page 10 of 14

V002.6

# Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time	_	
Ethyl 2-cyanoacrylate	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute
7085-85-0				Dermal Irritation / Corrosion)

# Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Ethyl 2-cyanoacrylate	irritating	72 h	rabbit	OECD Guideline 405 (Acute
7085-85-0				Eye Irritation / Corrosion)
Phthalic anhydride	highly irritating		rabbit	
85-44-9				

# ${\bf Respiratory\ or\ skin\ sensitization:}$

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising		guinea pig	
Hydroquinone 123-31-9	sensitising	Guinea pig maximisat ion test	guinea pig	
Phthalic anhydride 85-44-9	sensitising	in vivo	guinea pig	
Phthalic anhydride 85-44-9	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	Mouse local lymphnode assay (LLNA)

# Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Hydroquinone 123-31-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Phthalic anhydride 85-44-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		

# Repeated dose toxicity

Hazardous components CAS-No.	Result		Route of application	Exposure time / Frequency of treatment	Species	Method
Hydroquinone 123-31-9	LOAEL=<= 5 mg/kg	500	oral: gavage	14 days5 days/week. 12 doses	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Hydroquinone 123-31-9	NOAEL=>= 2 mg/kg	250	oral: gavage	14 days5 days/week. 12 doses	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

MSDS-No.: 173363 LOCTITE 4105 Page 11 of 14

V002.6

# **SECTION 12: Ecological information**

### General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

# 12.1. Toxicity

### **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
			Study			
Hydroquinone	LC50	0,17 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
123-31-9					Danio rerio)	203 (Fish, Acute
						Toxicity Test)
Hydroquinone	EC50	0.29  mg/l	Daphnia	48 h	Daphnia magna	
123-31-9			1		1 0	
Hydroquinone	EC50	0,335 mg/l	Algae	3 d	Selenastrum capricornutum	OECD Guideline
123-31-9		· ·			(new name: Pseudokirchnerella	201 (Alga, Growth
					subcapitata)	Inhibition Test)
Hydroquinone	NOEC	0,0057 mg/l	chronic	21 d	Daphnia magna	OECD 211
123-31-9		· ·	Daphnia			(Daphnia magna,
			-			Reproduction Test)
Phthalic anhydride	LC50	313 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
85-44-9		C				
Phthalic anhydride	EC50	68 mg/l	Algae	72 h	Selenastrum sp.	OECD Guideline
85-44-9		· ·			•	201 (Alga, Growth
						Inhibition Test)

# 12.2. Persistence and degradability

# Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Ethyl 2-cyanoacrylate 7085-85-0		aerobic	57 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydroquinone 123-31-9	readily biodegradable	aerobic	75 - 81 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
Phthalic anhydride 85-44-9		aerobic	90 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

# 12.3. Bioaccumulative potential / 12.4. Mobility in soil $\,$

### Mobility:

Cured adhesives are immobile.

### **Bioaccumulative potential:**

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Ethyl 2-cyanoacrylate 7085-85-0	0,776				22 °C	EU Method A.8 (Partition Coefficient)
Hydroquinone 123-31-9	1,03					
Phthalic anhydride 85-44-9	1,6					

### 12.5. Results of PBT and vPvB assessment

MSDS-No.: 173363 LOCTITE 4105 Page 12 of 14

V002.6

Hazardous components	PBT/vPvB
CAS-No.	
Hydroquinone	Not fulfilling PBT (persistent/bioaccummulative/toxic) criteria
123-31-9	
Phthalic anhydride	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
85-44-9	Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Product disposal:

Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations.

### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

MSDS-No.: 173363 LOCTITE 4105 Page 13 of 14

V002.6

# **SECTION 14: Transport information**

#### 14.1. UN number

ADR Not dangerous goods
RID Not dangerous goods
ADNR Not dangerous goods
IMDG Not dangerous goods

IATA 3334

### 14.2. UN proper shipping name

ADR Not dangerous goods
RID Not dangerous goods
ADNR Not dangerous goods
IMDG Not dangerous goods

IATA Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

#### 14.3. Transport hazard class(es)

ADR Not dangerous goods
RID Not dangerous goods
ADNR Not dangerous goods
IMDG Not dangerous goods

IATA 9

### 14.4. Packaging group

ADR Not dangerous goods
RID Not dangerous goods
ADNR Not dangerous goods
IMDG Not dangerous goods

IATA III

### 14.5. Environmental hazards

ADR not applicable
RID not applicable
ADNR not applicable
IMDG not applicable
IATA not applicable

### 14.6. Special precautions for user

ADR not applicable RID not applicable ADNR not applicable IMDG not applicable

IATA Primary packs containing less than 500ml are unregulated by this mode of transport

and may be shipped unrestricted.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (1999/13/EC) < 3 %

#### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

MSDS-No.: 173363 LOCTITE 4105 Page 14 of 14

V002.6

### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R22 Harmful if swallowed.

R36/37/38 Irritating to eyes, respiratory system and skin.

R37/38 Irritating to respiratory system and skin.

R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

R42/43 May cause sensitization by inhalation and skin contact.

R43 May cause sensitisation by skin contact.

R50 Very toxic to aquatic organisms.

R68 Possible risk of irreversible effects.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

# **Annex - Exposure Scenarios:**

Exposure Scenarios for ethyl 2-cyanoacrylate can be downloaded under the following link:

http://mymsds.henkel.com/mymsds/.470833..en.ANNEX\_DE.15743123.0.DE.pdf

Alternatively they can be accessed on the internet site www.mymsds.henkel.com by entering number 470833.



# Safety Data Sheet according to Regulation (EC) No1907/2006

Page 1 of 11

SDS No.: 179508

V006.1 Revision: 13.05.2014

printing date: 02.04.2015

Loctite 7455

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Loctite 7455

#### **Contains:**

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Primer

### 1.3. Details of the supplier of the safety data sheet

Henkel Limited

2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 Fax-no.: +44 1606 863762

ua-products a fety.uk@uk.henkel.com

### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification (CLP):

Flammable aerosol.	Category 1
H222 Extremely flammable aerosol.	
H229 Pressurised container: May burst if heated.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central Nervous System	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

MSDS-No.: 179508 Loctite 7455 Page 2 of 11

V006.1

# Classification (DPD):

F+ - Extremely flammable

R12 Extremely flammable.

Xi - Irritant

R38 Irritating to skin.

N - Dangerous for the

environment

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

### 2.2. Label elements

# **Label elements (CLP):**



Signal word:	Danger
Hazard statement:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Precautionary statement:	P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P211 Do not spray on an open flame or other ignition source. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P102 Keep out of reach of children.
Precautionary statement: Prevention	P261 Avoid breathing spray. P273 Avoid release to the environment.
Precautionary statement: Response	P302+P352 IF ON SKIN: Wash with plenty of soap and water.

MSDS-No.: 179508 Loctite 7455 Page 3 of 11

V006.1

### Label elements (DPD):

F+ - Extremely flammable

Xi - Irritant

N - Dangerous for the environment







### Risk phrases:

R12 Extremely flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

#### Safety phrases:

S23 Do not breathe spray.

S28 After contact with skin, wash immediately with plenty of water and soap.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

#### Additional labeling:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children

### 2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

# **SECTION 3: Composition/information on ingredients**

### General chemical description:

Primer

MSDS-No.: 179508 Loctite 7455 Page 4 of 11

V006.1

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	300-230-4 01-2119475515-33	>= 75-<100 %	Aspiration hazard 1 H304 Skin irritation 2 H315 Flammable liquids 2 H225 Specific target organ toxicity - single exposure 3; Inhalation H336 Chronic hazards to the aquatic environment 2 H411
Propane 74-98-6	200-827-9 01-2119486944-21	>= 10-< 25 %	Flammable gases 1 H220 Gases under pressure
N,N-Dimethyl-p-toluidine 99-97-8	202-805-4	>= 0,3-< 1 %	Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 3 H412 Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Acute toxicity 3; Oral H301

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Hydrocarbons, C7, n-alkanes,	300-230-4	>= 75 - < 100 %	Xn - Harmful; R65
isoalkanes, cyclics	01-2119475515-33		Xi - Irritant; R38
93924-37-9			F - Highly flammable; R11
			R67
			N - Dangerous for the environment; R51/53
Propane	200-827-9	>= 10 - < 25 %	F+ - Extremely flammable; R12
74-98-6	01-2119486944-21		
N,N-Dimethyl-p-toluidine	202-805-4	>= 0,3 -< 1 %	T - Toxic; R23/24/25
99-97-8			R33
			R52/53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

MSDS-No.: 179508 Loctite 7455 Page 5 of 11

V006.1

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

Vapors may cause drowsiness and dizziness.

Prolonged or repeated contact may cause eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

#### Extinguishing media which must not be used for safety reasons:

None known

#### 5.2. Special hazards arising from the substance or mixture

In case of fire, keep containers cool with water spray.

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

In case of fire toxic gases can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

### Additional information:

In case of fire, keep containers cool with water spray.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

Remove sources of ignition.

Ensure adequate ventilation.

# 6.2. Environmental precautions

Do not let product enter drains.

### 6.3. Methods and material for containment and cleaning up

Wipe up using absorbent material.

Store in a partly filled, closed container until disposal.

# **6.4.** Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin and eye contact.

Keep away from sources of ignition - no smoking.

Vapours should be extracted to avoid inhalation.

### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

MSDS-No.: 179508 Loctite 7455 Page 6 of 11

V006.1

### 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place.

Do not store near sources of heat or ignition, or reactive materials.

### 7.3. Specific end use(s)

Primer

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### **Occupational Exposure Limits**

Valid for

Great Britain

None

#### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	worker	Dermal	Long term exposure - systemic effects		300 mg/kg bw/day	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	worker	inhalation	Long term exposure - systemic effects		2085 mg/m3	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	general population	Dermal	Long term exposure - systemic effects		149 mg/kg bw/day	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	general population	oral	Long term exposure - systemic effects		149 mg/kg bw/day	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	general population	inhalation	Long term exposure - systemic effects		477 mg/m3	

#### **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

MSDS-No.: 179508 Loctite 7455 Page 7 of 11

V006.1

Eye protection:

Wear protective glasses.

Skin protection:

Suitable protective clothing

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance liquid colourless
Odor Aliphatic

Odour threshold No data available / Not applicable

pH not applicable

Initial boiling point 96 - 98 °C (204.8 - 208.4 °F)
Flash point Not applicable to aerosols.

Decomposition temperature No data available / Not applicable

Vapour pressure 46,7 mbar Density 0,68 g/cm3

()

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable

Solubility (qualitative) Not miscible

(Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable No data available / Not applicable Flammability No data available / Not applicable Auto-ignition temperature Explosive limits No data available / Not applicable No data available / Not applicable Partition coefficient: n-octanol/water Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Strong oxidizing agents.

# 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

No decomposition if used according to specifications.

### 10.5. Incompatible materials

See section reactivity

# 10.6. Hazardous decomposition products

None if used for intended purpose.

MSDS-No.: 179508 Loctite 7455 Page 8 of 11

V006.1

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Oral toxicity:

Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

#### Inhalative toxicity:

May cause headache and dizziness.

#### Skin irritation:

Causes skin irritation.

#### Eye irritation:

Prolonged or repeated contact may cause eye irritation.

#### Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Hydrocarbons, C7, n-	LD50		oral		rat	OECD Guideline 401 (Acute
alkanes, isoalkanes,						Oral Toxicity)
cyclics						-
93924-37-9						

### Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Hydrocarbons, C7, n-	LC50	> 23,3 mg/l	inhalation		rat	OECD Guideline 403 (Acute
alkanes, isoalkanes,						Inhalation Toxicity)
cyclics						-
93924-37-9						

#### Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 93924-37-9	LD50	> 2.920 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)

#### Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Propane	negative with	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
74-98-6	metabolic	chromosome			Mammalian Chromosome
	activation	aberration test			Aberration Test)

# **SECTION 12: Ecological information**

#### **General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

MSDS-No.: 179508 Loctite 7455 Page 9 of 11

V006.1

### 12.1. Toxicity

### **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Toxic to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
			Study			
Hydrocarbons, C7, n-alkanes,	EC50	3 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
isoalkanes, cyclics		_				202 (Daphnia sp.
93924-37-9						Acute
						Immobilisation
						Test)
Hydrocarbons, C7, n-alkanes,	NOEC	0,17 mg/l	chronic	21 d	Daphnia magna	OECD 211
isoalkanes, cyclics			Daphnia			(Daphnia magna,
93924-37-9			1 -			Reproduction Test)

# 12.2. Persistence and degradability

# Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
Hydrocarbons, C7, n-alkanes,	readily biodegradable	aerobic	98 %	OECD Guideline 301 F (Ready
isoalkanes, cyclics				Biodegradability: Manometric
93924-37-9				Respirometry Test)

### 12.3. Bioaccumulative potential / 12.4. Mobility in soil

#### **Mobility:**

The product is insoluble and sinks in water.

# **Bioaccumulative potential:**

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
N,N-Dimethyl-p-toluidine 99-97-8	2,81				25 °C	

### 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
Hydrocarbons, C7, n-alkanes, isoalkanes,	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
cyclics	Bioaccumulative (vPvB) criteria.
93924-37-9	
Propane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
74-98-6	Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

MSDS-No.: 179508 Loctite 7455 Page 10 of 11

V006.1

### Product disposal:

Dispose of according to regulations.

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

14 06 03 Other solvents and solvent mixtures

# **SECTION 14: Transport information**

# 14.1. UN number

ADR	1950
RID	1950
ADNR	1950
IMDG	1950
IATA	1950

# 14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADNR	AEROSOLS
IMDG	AEROSOLS (n-Heptane)
IATA	Aerosols, flammable

# 14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADNR	2.1
IMDG	2.1
IATA	2.1

# 14.4. Packaging group

ADR RID ADNR IMDG IATA

### 14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADNR	Environmentally Hazardous
IMDG	Environmentally Hazardous
IATA	not applicable

IATA not applicable

### 14.6. Special precautions for user

ADR not applicable

MSDS-No.: 179508 Loctite 7455 Page 11 of 11

V006.1

Tunnelcode: (D)

RID not applicable
ADNR not applicable
IMDG not applicable
IATA not applicable

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 100 (1999/13/EC)

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R11 Highly flammable.

R12 Extremely flammable.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R33 Danger of cumulative effects.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.