

## Olympic Wire and Cable

7 Madison Road • Fairfield, NJ 07004

973.227.7996 800.526.2269 • Fax: 973.227.1606

email: sales@olympicwire.com

# Olympic P/N 8032, DLO 2KV Diesel Locomotive Car Wire



## DLO 2KV Diesel Locomotive Car Wire

### Industrial Motor Lead Cable

Meets Flame Test Requirements of MSHA

Passes ICEA Cold Bend test at -40°C

Extra flexible stranded tinned Copper conductor, separator layer and EPDM insulation, chlorosulfonated polyethylene (CSPE) jacket

### Applications:

For use in diesel and electric locomotives, transit cars, earth-moving equipment, and oil rigging

## SPECIFICATIONS

Conductor Size	14 AWG
Stranding	19/27, Tinned Copper
Insulation	EPR
Insulation Thickness	0.047 in
Jacket	CPE
Jacket Thickness	0.020 in
Nom. O.D.	0.20 in
UL Style	RHH, RHW-2
UL Rating	600 V, -40°C to 90°C
UL Flame Test	VW-1
CSA Rating	1kV, -40°C to 90°C
CSA Type	RW-90
CSA Flame Test	FT-4
Color Code	Hook Up Wire Color Code Chart

RoHS Compliant



RoHS Compliant