

# C4700 Series

2500 WATTS (AC) DC/DC SINGLE OUTPUT

## Features

- Single Output
- 6U x 28TE x 306mm
- Weight 9.0kg



## Selection Tables

INPUT VDC										OUTPUT VDC	
10-16	OUTPUT	20-32	OUTPUT	40-64	50-80	OUTPUT	80-160	160-320	OUTPUT	MIN	MAX
	AMPS		AMPS			AMPS			AMPS		
C 4700	100	C 4720	160(1)	C 4730	C 4740	180(1)	C 4750	C 4770	180(1)	4,5	5,5
C 4701	80	C 4721	110	C 4731	C 4741	140	C 4751	C 4771	150	8	10
C 4702	68	C 4722	95	C 4732	C 4742	120	C 4752	C 4772	130	11	13
C 4703	58	C 4723	80	C 4733	C 4743	100	C 4753	C 4773	110	14	16
C 4704	46	C 4724	60	C 4734	C 4744	75	C 4754	C 4774	80	23	26
C 4705	40	C 4725	50	C 4735	C 4745	65	C 4755	C 4775	70	26	30
C 4706	18	C 4726	25	C 4736	C 4746	31	C 4756	C 4776	33	58	68
C 4707	10	C 4727	13	C 4737	C 4747	18	C 4757	C 4777	20	100	130
C 4708	5	C 4728	7	C 4738	C 4748	10	C 4758	C 4778	10	200	250
C 4709	22	C 4729	30	C 4739	C 4749	38	C 4759	C 4779	40	45	55

INPUT VAC					OUTPUT VDC	
185-264	93-138 185-264	3 X 400 (320-460)	3 X 480 (400-530)	OUTPUT AMPS	MIN.	MAX.
C 4780	C 4790	C 4780 V	C 4790 V	180(1)	4,5	5,5
C 4781	C 4791	C 4781 V	C 4791 V	150	8	10
C 4782	C 4792	C 4782 V	C 4792 V	130	11	13
C 4783	C 4793	C 4783 V	C 4793 V	110	14	16
C 4784	C 4794	C 4784 V	C 4794 V	80	23	26
C 4785	C 4795	C 4785 V	C 4795 V	70	26	30
C 4786	C 4796	C 4786 V	C 4796 V	33	58	68
C 4787	C 4797	C 4787 V	C 4797 V	20	100	130
C 4788	C 4798	C 4788 V	C 4798 V	10	200	250
C 4789	C 4799	C 4789 V	C 4799 V	40	45	55

(1) Suited for wall-mount, alternatives upon request

# C4700 Series

2500 WATTS (AC) DC/DC SINGLE OUTPUT

## Technical Illustrations C4700

