

## PCB D-SUB CONNECTORS





JD PDF

## TE CONNECTIVITY (TE) 25 HTMSFL ASSY RA 318 (IN,BL) AMPLIMITE | Standard

5788800-2 TE Internal Number: 5788800-2

Always EU RoHS/ELV Compliant

Connector Style **Receptacle** Centerline (mm) **2.761** Number of Positions **25** Number of Rows **2** 

Shell Size 3

Product Drawings	RCPT ASSEMBLY, SIZE 3, .318 SERIES, WITH FRONT METAL SHELL, HIGH TEMPERATURE, AMPLIMITE HD-20 PDF English
CAD Files	Customer View Model 2D_DXF.ZIP English
	Customer View Model 3D_IGS.ZIP English
	Customer View Model 3D_STP.ZIP English
	3D PDF PDF English
Catalog Pages/Data Sheets	AMPLIMITE Subminiature D Connectors - Right-Angle Posted Connectors PDF English
Product Environmental Compliance	
TE Material Declaration	MD_5788800-2_06302014013_dmtec PDF English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

## Receptacle

Shell Size

3

	Profile	Standard
	PCB Mounting Orientation	Right Angle
	Grounding Straps	With
	Shell Type	Front Metal Shell
	Footprint	8.08 mm [ .318 in ]
	Grounding Indents	Without
	Applies To	Printed Circuit Board
	Sealed	No
	Product Type	Connector
Configuration Features	Number of Positions	25
	Number of Rows	2
	Preloaded	Yes
Body Features	Plastic	Νο
	Color Code	None
	Eyelet Plating Material	Tin
	Shell Plating Material	Tin
	Insert Material	Zinc
	Shell Material	Steel
	Eyelet Material	Brass
	Post Size (in)	.026
	Post Size (in)	.020
Contact Features	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Copper Alloy
	Contact Mating Area Plating Material	Gold Flash
Termination Features	Termination Post Length	3.18 mm [ .125 in ]
	Grounding Clips	Without
Mechanical Attachment	PCB Mounting Style	Surface Mount, Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Boardlocks
	Mating Connector Lock	With
	Mating Connector Lock Type	Threaded Inserts
	Panel Mount Retention	Without
	Matine Detention Tune	Thursday Income

	iviating ketention Type	Inreaded inserts
	Boardlock Material	Copper Alloy
	Mating Retention	With
	PCB Mount Alignment	With
	Mounting Hole Diameter (mm)	3.18
	Boardlock Plating Material	Tin
	Threaded Insert Material	Zinc
	Mating Alignment	With
	Threaded Insert Plating Material	Clear Chromate
Housing Features	Centerline (mm)	2.761
	Housing Color	Black
	Housing Material	Thermoplastic
Dimensions	PCB Thickness (Recommended)	1.57 mm [ .062 in ]
Usage Conditions	High Temperature Housing	Yes
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Тгау
	Packaging Quantity	65
Product Compliance	Statement of Compliance	
	VIEW ALL PRODUCT COMPLIANCE	
Producto 11 Day Ita		View All Compare 0/10
Products - 11 Results		
Relation Type 🛛 🔻		
RELATIONSHIP Mating Products		
Used to identify Mating Parts		See All Mating Products
PR	CODUCT - MATING PRODUCTS	www.Ell.Rel/S/ElV.Compliant

Aller .

Connectors - IDC D-Sub Connectors AMPLIMITE | HDE (IDC) Insulation 25 HDF MS PILIG 22-26 Connector Stude Plus

Always EU RoHS/ELV Compliant





✓ Active

Connector Style **Flug** 

- Centerline 1.38 mm
- Number of Positions 25
- Number of Rows **2**
- Preloaded **Yes**

## RELATIONSHIP **Mating Products** Used to identify Mating Parts See All Mating Products PRODUCT - MATING PRODUCTS Connectors - PCB D-Sub Connectors AMPLIMITE | Standard Always EU RoHS/ELV Compliant 25 MSFL PLUG RA 318 Connector Style Plug (SL, FM, BL) - 5747842-5 TE INTERNAL NUMBER: 5747842-5 Centerline 2.77 mm Number of Positions 25 ✓ Active Number of Rows 2 Shell Size 3 RELATIONSHIP **Mating Products** See All Mating Products Used to identify Mating Parts PRODUCT - MATING PRODUCTS Connectors - PCB D-Sub Connectors Always EU RoHS/ELV Compliant AMPLIMITE 25 MSFL PLUG RA 318 Connector Style Plug (IN, FM, BL) - 5747842-3 TE INTERNAL NUMBER: 5747842-3 Centerline 2.77 mm Number of Positions 25 ✓ Active Number of Rows 2 Shell Size 3