

Customer Information Sheet

DRAWING No.: M80-867XXXX

SHEET 2 OF 2

IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

SPECIFICATIONS:**MATERIAL:**MOULDING = GLASS-FILLED POLYESTER,
UL94V-0, BLACK

CONTACTS = PHOSPHOR BRONZE

LATCHES = BERYLLIUM COPPER

FINISH:**CONTACTS:**

05 = 0.75µ GOLD

22 = 0.75µ GOLD ON CONTACT AREA.

3.0µ 90/10 TIN/LEAD ON TAILS

LATCH = 1.25µ NICKEL

ELECTRICAL:

CURRENT RATING (25°C) = 3.0A MAX.

CURRENT RATING (85°C) = 2.2A MAX.

WORKING VOLTAGE = 800V AC/DC

VOLTAGE PROOF = 1200V AC/DC

CONTACT RESISTANCE:

INITIAL = 20mΩ MAX.

AFTER CONDITIONING = 25mΩ MAX.

INSULATION RESISTANCE:

INITIAL = 1000MΩ MIN.

AFTER CONDITIONING = 100MΩ MIN.

MECHANICAL:




DURABILITY = 500 OPERATIONS

ENVIRONMENTAL:

TEMPERATURE RANGE = -55°C TO +125°C

PACKING:

TUBE

FOR COMPLETE SPECIFICATION, SEE
COMPONENT SPEC C005XX (LATEST ISSUE)**NOTES:**

- 2-OFF STRAIN RELIEF STRAPS M80-0030006 MAY BE USED WITH THIS CONNECTOR.
- FOR RoHS COMPLIANT EQUIVALENT PRODUCT USE M80-853XXXX CONNECTORS.

ORDER CODE:**M80-867XXXX****TOTAL No. OF CONTACTS:**04, 06, 08, 10, 12, 14,
16, 18, 20, 26, 34, 44**FINISH:**

05 = GOLD

22 = SELECTIVE GOLD

BRITISH STANDARD ORDER CODE:**B5743-2XX-M-T-X****TOTAL No. OF CONTACTS:**04, 06, 08, 10, 12, 14, 16,
18, 20, 26, 34, 44**FINISH:**

1 = SELECTIVE GOLD

3 = GOLD

HARWINwww.harwin.com
technical@harwin.comTHIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.**TOLERANCES**X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm

ANGLES = ±5°

UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH:

SEE ABOVE

S/AREA:mm²**TITLE:**DATAMATE DIL
VERTICAL MALE PC TAIL
ASSEMBLY - LATCHED**DRAWING NUMBER:****M80-867XXXX**SHT
2
OF
2

SB	16	15.11.13	12240
NAME	ISS.	DATE	C/NOTE
APPROVED: S.BENNETT			
CHECKED: M.PLESTED			
DRAWN: J. CLAY			
CUSTOMER REF.:			
ASSEMBLY DRG:			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Harwin:

[M80-8674422](#) [M80-8670405](#) [M80-8672622](#) [M80-8671222](#) [M80-8672022](#) [B5743-218-M-T-1](#) [B5743-208-M-T-1](#)
[M80-8671605](#) [B5743-214-M-T-1](#) [B5743-210-M-T-1](#) [B5743-216-M-T-1](#) [B5743-212-M-T-1](#) [B5743-234-M-T-1](#) [B5743-](#)
[206-M-T-1](#) [B5743-204-M-T-1](#) [B5743-226-M-T-1](#) [B5743-220-M-T-1](#) [M80-8670605](#) [M80-8670805](#) [M80-8672005](#) [M80-](#)
[8673405](#) [M80-8673422](#) [M80-8671022](#) [M80-8670622](#) [M80-8670822](#) [M80-8670422](#) [M80-8671822](#) [M80-8671422](#)
[M80-8671205](#) [M80-8671622](#) [B5743-220-M-T-3](#) [M80-8672605](#)