


REV.	ECN NO.	DATE	SIGN	DESCRIPTION

ALTW

CONFIDENTIAL

2014-10-24

R&D DEPT.






ALTW

DCC. DEPT.


CONFIDENTIAL

2014.11.26


ISSUED



- Note:
- * $\varnothing$ Important Dimension To Check.
 - * Waterproof Rate: IP68
 - * Working Voltage Rating: AC 300 V
 - * Working Current Rating: 5A
 - * Flame Class: UL94V-0 (UV Resistance)
 - * Housing: Nylon+GF, Black
 - * Male Pin: Copper Alloy, Gold Plated
 - * Nut: Nylon+GF, Black
 - * Gasket: Silicone, Gary
 - * Use Without Waterproof Cap
Panel Thickness Max: 4.0mm
 - * Use With Waterproof Cap
Panel Thickness Max: 3.0mm



Pin Assignments
Front View



Recommended Panel Cut-out

A	UNIT:mm		TOLERANCE .X ±0.25		TITLE X Lok B-Size Receptacle Front Fastened M Conn M 5 Pin				Amphenol LTW		ITEM NO BD-05PMMS-QC8001	DRAWN BY Micky	DATE 2014-10-24
	SCALE 2:1		SIZE A4		SHEET 1 OF 1				安費諾亮泰企業股份有限公司		DWG NO BD-05PMMS-QC8001	CHECKED BY Spring	DATE 2014-10-24
	REV. A		WC-REV. A.1		$\varnothing$ Inspection item						CUSTOMER ALTW	APPROVED BY Kevin	DATE 2014-10-24
													8 FMW10702-01-02A1

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.