


8NUMBER FCI	TYPE PRODUCT SPECIFICATION	GS-12-607	
TITLE SUB COMPACT- D RIGHT ANGLE PIP FCI P/N :CD- - S 13 E6 R- -- LF CD- - S 13 M6 R- -- LF		PAGE 1 of 7	REVISION A
		AUTHORIZED BY Anish Salam	DATE 14-Mar-09
		CLASSIFICATION UNRESTRICTED	

COMPACT- D PIP



8NUMBER 	TYPE PRODUCT SPECIFICATION	GS-12-607	
TITLE SUB COMPACT- D RIGHT ANGLE PIP FCI P/N :CD- - S 13 E6 R- -- LF CD- - S 13 M6 R- -- LF		PAGE 2 of 7	REVISION A
		AUTHORIZED BY Anish Salam	DATE 14-Mar-09
		CLASSIFICATION UNRESTRICTED	

CONTENTS

1. Objective	2
2. Scope.....	2
3. Product description	0
3.1 General	0
3.2 Design and construction	3
3.3 Materials and plating.....	4
3.3.1 Housing dielectric material	4
3.3.2 Terminal material	4
3.3.3 Terminal Plating	4
3.3.4 Shell material	4
3.3.5 Shell Plating	4
3.3.6 Accessory Material	4
3.3.7 Accessory Plating	4
4. Characteristics	4
4.1 Climatic category	
4.2 Electrical characteristics	5
4.2.1 Voltage proof.....	5
4.2.2 Current carrying capacity.....	5
4.2.3 Initial contact resistance.....	5
4.2.4 Initial insulation resistance.....	5
4.3 Mechanical characteristics.....	6
4.3.1 Mechanical operation.....	6
4.3.2 Insertion and withdrawal force.....	6
4.3.3 Insert retention in housing (axial).....	6
4.3.4 Vibration.....	6
4.4 Accessories.....	7
5. Reflow process	7
Lead free soldering	7
6. Packaging	7
7.Revision record	7

8NUMBER FCI	TYPE PRODUCT SPECIFICATION	GS-12-607	
TITLE SUB COMPACT- D RIGHT ANGLE PIP FCI P/N :CD- - S 13 E6 R- -- LF CD- - S 13 M6 R- -- LF		PAGE 3 of 7	REVISION A
		AUTHORIZED BY Anish Salam	DATE 14-Mar-09
		CLASSIFICATION UNRESTRICTED	

1.0 OBJECTIVE

This specification defines the performance, test, and reliability requirements of the Compact-D PIP connectors


2.0 SCOPE

This product specification covers the requirements of a SUB Compact- D PIP Right Angle.
For Product Pick Process: Hand Placing / Gripper / Vacuum Nozzle

3. Product description

3.1 General

PRODUCT LEAD FREE IN ACCORDANCE TO RoHS 2002/EC/95



3.2 Design and construction

The connector shall be of design, construction and physical dimensions as specified on the applicable product customer drawings:

US STANDARD 14,15,26& 44 POS

C-CD-0022 FOR THE P/N CD--S13E6RL/RX/RV--LF
C-DD-0025 FOR THE P/N CD--S13M6RL/RX/RV—LF

8NUMBER 	TYPE PRODUCT SPECIFICATION	GS-12-607	
TITLE SUB COMPACT- D RIGHT ANGLE PIP FCI P/N :CD- - S 13 E6 R- -- LF CD- - S 13 M6 R- -- LF		PAGE 4 of 7	REVISION A
		AUTHORIZED BY Anish Salam	DATE 14-Mar-09
		CLASSIFICATION UNRESTRICTED	

3.3 Materials and plating

3.3.1 Housing dielectric material

Plastic raw material: Genestar, 33% glass fiber, UL94 V-O rating
Black colour

3.3.2 Terminal material

Copper Alloy CuSn8

3.3.3 Terminal Plating

Gold over Nickel on mating area metal
Tin over Nickel on termination

3.3.4 Shell material

Steel

3.3.5 Shell Plating

Nickel over Copper

3.3.6 Accessory Material

Brass

3.3.7 Accessory Plating

LIF Metal Peg:- Pure Tin over Nickel.
Female Screw, Insert & Metal Bracket: Nickel Sulfamate.

4. Characteristics

4.1 Climatic category

Performance level	Category Temperature		Damp heat , Steady state		Days
	Lower ° C	Upper ° C	Temp ° C	Rel. Humidity	
1	-55	125	40	93%	56
2	-55	100	40	93%	21

8NUMBER 	TYPE PRODUCT SPECIFICATION	GS-12-607	
TITLE SUB COMPACT- D RIGHT ANGLE PIP FCI P/N :CD- - S 13 E6 R- -- LF CD- - S 13 M6 R- -- LF		PAGE 5 of 7	REVISION A
		AUTHORIZED BY Anish Salam	DATE 14-Mar-09
		CLASSIFICATION UNRESTRICTED	

4.2 Electrical Characteristics

4.2.1 Voltage proof

Conditions: IES 512-2

Standard atmospheric conditions

Mated connectors

Wiring according to 8.1.5

Contacts/Contacts: 1000 V r.m.s

Contact/Test panel: 1200 V r.m.s

4.2.2 Current carrying capacity

Conditions: IES 512-3

Standard atmospheric conditions

Rated current when all contacts are loaded.

Terminations are wired with 0.5mm² wire.

4.2.3 Initial contact resistance

Conditions: IES 512-2

Standard atmospheric conditions

Mated connectors

Connection points acc. To 8.1.1

Max. Value of contact resistance 25mΩ*

* Max. rise 10mΩ in relation to initial values in other tests.

4.2.4 Initial insulation resistance

Conditions: IES 512-2

Standard atmospheric conditions

Mated connectors

Test Voltage: 100V±15V d.c

All performance levels : 5 GΩ min.

8NUMBER FCI	TYPE PRODUCT SPECIFICATION	GS-12-607	
TITLE SUB COMPACT- D RIGHT ANGLE PIP FCI P/N :CD- - S 13 E6 R- -- LF CD- - S 13 M6 R- -- LF		PAGE 6 of 7	REVISION A
		AUTHORIZED BY Anish Salam	DATE 14-Mar-09
		CLASSIFICATION UNRESTRICTED	

4.3. Mechanical

4.3.1 Mechanical operation

Conditions: IEC 512-5
Speed: 10mm/s max.
Rest: 10 s min. (unmated)

Performance level	Operations
1	500
2	200

4.3.2 Insertion and withdrawal forces

Conditions: IEC 512-7

Sl.No.	Number of contacts	Insertion and withdrawal force				
		withdrawal		Min. 0.3N/Cts. with pin Ø 0.99mm	Insertion	
		Min.N	Max.N		Max. N	Max. 3.3N/Cts. with pin Ø 0.99mm
1	14/15	3.3	20		30	
2	26	4.5	33		50	
3	44	7.8	56		83	

4.3.3 Insert retention in housing (axial)

Conditions: IEC 512-8

Number of contacts	F in N
14/15	53
26	80
44	124

4.3.4 Vibration

Conditions: IEC 512-4

Performance level	Severity
1	10Hz to 2000 Hz and 1.5mm or 20g. 3x2.5h
2	10Hz to 500 Hz and 0.35mm or 5g. 3x2h

8NUMBER 	TYPE PRODUCT SPECIFICATION	GS-12-607	
TITLE SUB COMPACT- D RIGHT ANGLE PIP FCI P/N :CD- - S 13 E6 R- -- LF CD- - S 13 M6 R- -- LF		PAGE 7 of 7	REVISION A
		AUTHORIZED BY Anish Salam	DATE 14-Mar-09
		CLASSIFICATION UNRESTRICTED	

4.4 Accessories

Insert M3 or UNC 4-40 : Retention against torque 0.7N.m Min.
 Female screw lock : Retention against torque 0.5N.m Min
 Metal PIP: Retention against force 15N

5. Reflow process

Lead free soldering

In accordance with : JSTD_020C

6. Packaging

In accordance with GS-14-1139 for Tape & Reel Packaging
 In accordance with GS-14-1157 for Tray Packaging

7.Revision record

Rev.	Page	Description	ECN	YY/MM/DD
A	ALL	NEW	I09-0040	09/03/14

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI:](#)

CD15S13E4RL09LF	CD15S13E4RL12LF	CD15S13E4RV09LF	CD15S13E4RV12LF	CD15S13E4RX09LF
CD15S13E6RL09LF	CD15S13E6RL12LF	CD15S13E6RV09LF	CD15S13E6RV12LF	CD15S13E6RX09LF
CD26S13E4RL09LF	CD26S13E4RL12LF	CD26S13E4RV09LF	CD26S13E4RV12LF	CD26S13E4RX09LF
CD26S13E4RX12LF	CD26S13E6RL09LF	CD26S13E6RL12LF	CD26S13E6RV09LF	CD26S13E6RV12LF
CD26S13E6RX09LF	CD26S13E6RX12LF	CD44S13E4RL09LF	CD44S13E4RL12LF	CD44S13E4RV09LF
CD44S13E4RV12LF	CD44S13E4RX09LF	CD44S13E4RX12LF	CD44S13E6RL09LF	CD44S13E6RL12LF
CD44S13E6RV09LF	CD44S13E6RV12LF	CD44S13E6RX09LF	CD44S13E6RX12LF	CD26S13M6RX12LF
CD14S13E6RV09LF	CD15S13E4RX12LF	CD15S13E6RX12LF		