

THIS IS ISSUED IN STRICT CONFIDENCE THAT IT IS NOT USED AS A BASIS FOR MANUFACTURE OR SALE AND THAT IT IS NOT COPIED, REPRINTED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE PRIOR WRITTEN CONSENT OF CAL TEST ELECTRONICS, INC.


REVISIONS			
REV.	DESCRIPTIONS	DATE	APPROVED
—	CLASS A RELEASED	10/13/03	

1. SAFETY JACK, REAR MOUNT, VERTICAL PCB, LONG PIN.
2. SPECIFICATIONS:
INSULATOR: POLYACETAL
CONTACT: BRASS, NICKEL PLATED
3. RATING:
VOLTAGE: 1,000 V CATIII P2 (IEC 61010-031)
CURRENT: 25A MAX.
RESISTANCE: <5mΩ.
TEMPERATURE: -20° C TO +80° C.
4. MOUNTING: REF. DIAGRAM
5. MAXIMUM PANEL THICKNESS: .12 (3).


PART NUMBER

CT3150-#

COLOR: 0 - BLACK
1 - BROWN
2 - RED
4 - YELLOW
5 - GREEN
6 - BLUE
7 - PURPLE
8 - GRAY
9 - WHITE



THIRD ANGLE PROJECTION



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS DECIMALS
± 1/32 .XX ± .02
XXX ± .005
DO NOT SCALE DRAWING

MATERIAL

FINISH

CONTRACT NO.

APPROVALS

DATE

DRAWN WDH

10/13/03

CHECKED

ENGR.

DESIGN ACTIVITY

Cal Test Electronics

22820 Savi Ranch Parkway
Yorba Linda, CA 92887-4610

TITLE

**4mm SAFETY JACK,
VERTICAL PCB MOUNT, LONG PIN**

SIZE
A

CAGE CODE

43F45

DWG. NO.

P315000

REV.

—

SCALE 1:1

SHEET 1 OF 1

NEXT ASSY

USED ON

APPLICATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Global Specialties:

[CT3150-0](#) [CT3150-8](#) [CT3150-2](#) [CT3150-9](#) [CT3150-6](#) [CT3150-5](#) [CT3150-4](#) [CT3150-7](#) [CT3150-1](#)